



Parts and Accessories Service and Repairs Resource Center Team NAPA

Current Vehicle

No Vehicle Selected
[Change Vehicle](#)

Search Catalog

Keyword

GO

NAPA Part No.

GO

Non-NAPA Part No.

GO



Shop NAPAonline

Material Safety Data Sheet (MSDS)

PRESTONE Power Steering Fluid AS-260 AS-261

Right parts for the job

[Job Type Search](#)

[Tools & Heavy Duty](#)

NAPA Locator

Enter Zip

- [Parts Store](#)
- [Repair Shop](#)
- [Collision Center](#)
- [Truck Center](#)

My Account

[Login](#)

[Create Account](#)



Are you saving with AAA?
[Click here to start saving!](#)

MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none
PRESTONE Power Steering Fluid AS-260 AS-261
Code: PPC Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: PRESTONE Power Steering Fluid AS-260 AS-261

MANUFACTURER'S NAME: EMERGENCY TELEPHONE NUMBER
Prestone Products Corporation (203)830-7865
39 Old Ridgebury Road
Danbury, CT 06810-5109 MISCELLANEOUS INFORMATION

Section 2 - Hazardous Ingredients

HAZARDOUS COMPONENTS CAS # PERCENT EXPOSURE LIMITS

Refined Petroleum	64741-88-4	0-95	5 mg/m3 TWA OSHA PEL
Distillates	64742-65-0	5	mg/m3 TWA ACGIH TLV
	64742-54-7		
	64742-56-9		
	64741-97-5		
	64742-55-8		

Proprietary Additive	Proprietary	0-10	5 mg/m3 TWA OSHA PEL
			5 mg/m3 TWA ACGIH TLV

MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none
PRESTONE Power Steering Fluid AS-260 AS-261
Code: PPC Page: 2

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Eye contact may cause irritation. Prolonged skin contact may cause irritation or dermatitis. Small amounts aspired into the lungs may cause lipid pneumonitis.

POTENTIAL HEALTH EFFECTS:

ACUTE HAZARDS:

Inhalation: Inhalation of the product is unlikely with normal usage. Prolonged exposure to mists or vapors in a poorly ventilated area may result in lipid pneumonitis.

Eye Contact: Direct eye contact may result in mild inflammation or irritation.

Ingestion: Ingestion of this product is not expected to result in any acute systemic toxic effects. If more than several mouthfuls are swallowed, abdominal discomfort, belching, nausea and diarrhea may occur. Aspiration

into the lungs during ingestion or vomiting following ingestion may cause lipid pneumonitis.

Chronic Hazards: Prolonged or repeated overexposure to oil mists may result in oil granuloma formation in the lung and increased incidence of infection. Prolonged or repeated inhalation or ingestion may lead to central nervous system effects, gastrointestinal disturbances and possible adverse reproductive effects.

Medical Conditions Aggravated By Exposure: Persons who are prone to acne or seborrhea are susceptible to blockage of hair follicles by insoluble oils. Folliculitis may develop. Comedones and perifollicular papules and pustules (oil boils) may occur. These effects should rapidly clear upon cession of exposure. Good housekeeping and personal hygiene should prevent these effects.

Carcinogen: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP or OSHA.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none

PRESTONE Power Steering Fluid AS-260 AS-261

Code: PPC Page: 3

=====

Section 4 - First Aid Measures

INHALATION: If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.

SKIN CONTACT: Remove contaminated clothing immediately. Wash all affected and exposed areas with soap and water. If skin irritation or redness develops and persists, seek medical attention.

EYE CONTACT: Exposed eyes should be immediately flushed with copious amounts of water using a steady stream for a minimum of 15 minutes. If irritation, pain, swelling or tearing develop, seek medical attention.

INGESTION: Do not induce vomiting because of risk of aspiration and lipid pneumonitis developing. Get medical assistance by calling a physician, emergency room or poison control center. The greatest hazard is aspiration pneumonitis.

NOTES TO PHYSICIAN: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and clinical conditions.

=====

Section 5 - Firefighting Measures

FLASH POINT: Greater than 300 deg. F (149 Deg. C)

AUTOIGNITION TEMPERATURE: Not Determined

FLAMMABILITY LIMITS: LEL: Not Determined UEL: Not Determined

EXTINGUISHING MEDIA: Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water. Avoid spraying water directly into containers.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

UNUSUAL FIRE HAZARDS: Keep away from excessive heat and open flames. Containers may rupture from excessive heat. Combustion products may be hazardous. Mists and sprays may be flammable below the product's normal flashpoint.

HAZARDOUS COMBUSTION PRODUCTS: Burning may produce carbon monoxide, oxides of sulfur and nitrogen and other products of incomplete combustion.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none

PRESTONE Power Steering Fluid AS-260 AS-261

Code: PPC Page: 4

=====

Section 6 - Environmental Release Measures

Eliminate all ignition sources. Wear appropriate protective clothing and equipment (See Section 8). Recover free product by pumping or collect with absorbent material and place in appropriate, labeled container for disposal. Keep out of sewers, watercourses and low areas.

=====
Section 7 - Handling and Storage

Avoid eye contact and prolonged skin contact.

Avoid breathing vapors, mists and fumes..

Use with adequate ventilation.

Wash exposed skin thoroughly with soap and water after use.

Keep container away from excessive heat and open flames.

Keep containers closed when not in use.

Store in a cool, dry area.

Empty containers retain product residue and may be hazardous. Do not cut, weld, drill, etc. containers, even empty. Do not reuse empty containers unless properly cleaned.

=====
Section 8 - Exposure Controls/Personal Protection

VENTILATION: Use local exhaust as required to maintain exposures below the occupational exposure limits.

RESPIRATORY PROTECTION: None under normal use conditions. For operations where the TLV for oil mist may be exceeded, a NIOSH/MSHA approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Neoprene gloves where prolonged skin contact may occur.

EYE PROTECTION: Safety glasses with sideshields or goggles are recommended.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none
PRESTONE Power Steering Fluid AS-260 AS-261
Code: PPC Page: 5

=====
Section 9 - Physical and Chemical Properties

APPEARANCE AND ODOR: Light amber or yellow liquid, mild odor.

pH: NA
BOILING POINT (F): NA
MELTING POINT (F): NA
SOLUBILITY IN WATER: Negligible
PERCENT VOLATILE: Negligible
SPECIFIC GRAVITY: 0.87 - 0/.88
VAPOR PRESSURE: Not determined
VAPOR DENSITY: Not determined
EVAPORATION RATE: Not available
VISCOSITY: Not available

=====
Section 10 - Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Avoid exposure to excessive heat and open flames.

INCOMPATIBILITY: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will product carbon monoxide, oxides of sulfur and nitrogen and othe rproducts of incomplete combustion.

HAZARDOUS POLYMERIZATION: Will not occur

Petroleum Distillates: No toxicity data avilable for this product at this time.

=====
Section 11 - Toxicological Information

=====
Section 12 - Ecological Information

No ecotoxicity data is available for this product or its components at this time.

=====
Section 13 - Disposal Considerations

Recycle, incinerate, treat or landfill in accordance with all local, state/provincial and federal regulations.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none
PRESTONE Power Steering Fluid AS-260 AS-261
Code: PPC Page: 6

=====
Section 14 - Transport Information

U.S. DOT HAZARD CLASSIFICATION

PROPER SHIPPING NAME: Not regulated
TECHNICAL NAME: N/A
UN NUMBER: N/A
HAZARD CLASS/PACKING GROUP: N/A
LABELS REQUIRED: N/A

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION

DESCRIPTION: Not regulated

ID NUMBER: N/A
HAZARD CLASS: N/A
PACKING GROUP: N/A
LABELS REQUIRED: N/A
PLACARDS REQUIRED: N/A

=====
Section 15 - Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Not applicable

EPA SARA 313 This Product Contains the Following Chemicals

Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

NONE

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65 - This product does not contain chemicals regulated under California Proposition 65.

EPA TSCA INVENTORY: All of the components of this material are listed on

the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 11-15-96 Revision Date: none
PRESTONE Power Steering Fluid AS-260 AS-261
Code: PPC Page: 7

=====

Section 16 - Other Information

NFPA RATING (NFPA 704) - FIRE:1
HEALTH: 1
REACTIVITY: 0

This MSDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of test conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact: James L. Ottowitz
Prestone Products Corp.
39 Old Ridgebury Road
Danbury, CT 06810-5109
(203) 830-7865

[Return to Previous Page](#)

[Return to top of page](#)



[About NAPAonline](#)

[Customer Support](#)

[Privacy/Legal](#)

[SiteMap](#)

©2006, National Automotive Parts Association

This site is best viewed using JavaScript-enabled Internet Explorer Version 5.0 and above.

NAPA Analytics