

ITEM: 1D493 - Spray Paint Color Aluminum Gloss F

PICK REQ: 1017992169

MATERIAL SAFETY DATA SHEET (MSDS)

MSDS: A7792

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - A7792

Associated Grainger Item: 1D493 - Spray Paint Color Aluminum Gloss F

MATERIAL SAFETY DATA SHEET

24 HOUR ASSISTANCE: 1-847-367-7700

RUST-OLEUM CORP.
WWW.RUSTOLEUM.COM

SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION

PRODUCT NAME:
RUST-OLEUM HIGH PERFORMANCE INDUSTRIAL ENAMEL AEROSOL - HIGH HEAT
(FORMERLY KNOWN AS HARD HAT)

IDENTIFICATION NUMBER: V2116838, V2176838

PRODUCT USE/CLASS: HIGH HEAT COATING/AEROSOL

REVISION DATE: 08/27/2004

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: CZICZO, RAY

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	WEIGHT %	LESS THAN
TOLUENE	108-88-3	35.0	
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0	
ACETONE	67-64-1	15.0	
ALUMINUM FLAKE	7429-90-5	10.0	
STODDARD SOLVENTS	8052-41-3	10.0	
XYLENE	1330-20-7	10.0	
PIGMENT BLACK 26	68186-94-7	10.0	
SUPER HIGH FLASH NAPHTHA	64742-95-6	5.0	
MAGNESIUM SILICATE	14807-96-6	5.0	
ETHYLBENZENE	100-41-4	5.0	
MANGANESE DIOXIDE	1313-13-9	5.0	

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
TOLUENE	50 PPM	150 PPM	200 PPM	300 PPM
LIQUEFIED PETROLEUM GAS	1000 PPM	N.E.	1000 PPM	N.E.
ACETONE	500 PPM	750 PPM	750 PPM	N.E.
ALUMINUM FLAKE	10 MG/M3	N.E.	15 MG/M3	N.E.
STODDARD SOLVENTS	100 PPM	N.E.	500 PPM	N.E.
XYLENE	100 PPM	150 PPM	100 PPM	N.E.
PIGMENT BLACK 26	10 MG/M3	N.E.	N.E.	N.E.
SUPER HIGH FLASH NAPHTHA	N.E.	N.E.	N.E.	N.E.
MAGNESIUM SILICATE	10 MG/M3	N.E.	15 MG/M3	N.E.
ETHYLBENZENE	100 PPM	125 PPM	100 PPM	N.E.
MANGANESE DIOXIDE	0.2 MG/M3	N.E.	5 MG/M3	N.E.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CONTENTS UNDER PRESSURE. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE - INHALATION:
HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND

LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED.

EFFECTS OF OVEREXPOSURE - INGESTION:
ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SUBSTANCE MAY BE HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:
IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO TOLUENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG AND SPLEEN DAMAGE. EFFECTS IN HUMANS HAVE INCLUDED LIVER AND CARDIAC ABNORMALITIES.

PRIMARY ROUTE(S) OF ENTRY:
SKIN CONTACT, SKIN ABSORPTION, INHALATION, EYE CONTACT

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT:
HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:
IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:
ASPIRATION HAZARD:
DO NOT INDUCE VOMITTING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (SETAFLASH): -156 F

LOWER EXPLOSIVE LIMIT: 1.0%
UPPER EXPLOSIVE LIMIT: 37.0%

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:
VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WATER SPRAY MAY BE INEFFECTIVE.
FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!
PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.
ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED.

SPECIAL FIREFIGHTING PROCEDURES:
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

SECTION 7 - HANDLING AND STORAGE

HANDLING:
WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR MIST.

STORAGE:
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:
USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS.

RESPIRATORY PROTECTION:
A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:
USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

PROTECTION:
SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:
REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:
WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 93 - 468 F
VAPOR DENSITY: HEAVIER THAN AIR
ODOR: SOLVENT LIKE
ODOR THRESHOLD: ND
APPEARANCE: LIQUID
EVAPORATION RATE: FASTER THAN ETHER
SOLUBILITY IN H2O: SLIGHT
FREEZE POINT: ND
SPECIFIC GRAVITY: 0.8210
VAPOR PRESSURE: ND
pH: NE
PHYSICAL STATE: LIQUID
(SEE SECTION 16 FOR ABBREVIATION LEGEND)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:
AVOID ALL POSSIBLE SOURCES OF IGNITION. FLAMMABLE HYDROGEN GAS WILL EVOLVE WHEN PRODUCT COMES IN CONTACT WITH WATER OR DAMP AIR. HEAT WILL BE GENERATED. THE AMOUNT OF HEAT GENERATED WILL DEPEND UPON THE VOLUME OF MATERIAL IN CONTACT. AVOID TEMPERATURES ABOVE 120 DEG. F.

INCOMPATIBILITY:
INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIS.

HAZARDOUS DECOMPOSITION:
IF HEATED TO DECOMPOSITION IT EMITS ACRID SMOKE AND IRRITATING FUMES. BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.
STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION 11 - TOXICOLOGICAL INFORMATION

PRODUCT LD50: ND
PRODUCT LC50: ND

CHEMICAL NAME	LD50	LC50
TOLUENE	N.D.	N.D.
LIQUEFIED PETROLEUM GAS	N.D.	N.D.
ACETONE	N.D.	N.D.
ALUMINUM FLAKE	N.D.	N.D.
STODDARD SOLVENTS	N.D.	N.D.
XYLENE	N.D.	N.D.
PIGMENT BLACK 26	>5000 MG/KG (ORAL, RAT)	N.D.
SUPER HIGH FLASH NAPHTHA	4700 MG/KG (ORAL, RAT)	3670 MG/KG (INH, RAT)
MAGNESIUM SILICATE	N.D.	TCLO: 11 MG/M3 INH.
ETHYLBENZENE	3500 MG/KG (ORAL, RAT)	N.D.
MANGANESE DIOXIDE	3478 MG/KG (ORAL, RAT)	N.D.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL INFORMATION:
DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: AEROSOL

PACKING GROUP:
DOT TECHNICAL NAME:
HAZARD SUBCLASS: 1
DOT HAZARD CLASS: 2
RESP. GUIDE PAGE: 126
DOT UN/NA NUMBER: UN 1950

SECTION 15 - REGULATORY INFORMATION

CERCLA - SARA HAZARD CATEGORY:
THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

SARA SECTION 313:
LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER
TOLUENE	108-88-3
XYLENE	1330-20-7
ETHYLBENZENE	100-41-4
MANGANESE DIOXIDE	1313-13-9

TOXIC SUBSTANCES CONTROL ACT:
LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES: NONE KNOWN

U.S. STATE REGULATIONS: AS FOLLOWS

NEW JERSEY RIGHT-TO-KNOW:
THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

CHEMICAL NAME	CAS NUMBER
SILICONIZED ALKYD RESIN	PROPRIETARY

PENNSYLVANIA RIGHT-TO-KNOW:
THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

CHEMICAL NAME	CAS NUMBER
SILICONIZED ALKYD RESIN	PROPRIETARY

CALIFORNIA PROPOSITION 65:

WARNING:
THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

CHEMICAL NAME	CAS NUMBER
ETHYLBENZENE	100-41-4
MICROCRYSTALLINE SILICA	14808-60-7
ARSENIC COMPOUNDS	NOT SPECIFIED
LEAD COMPOUNDS	NOT SPECIFIED
PROPYLENE OXIDE	75-56-9
ACETALDEHYDE	75-07-0
CADMIUM COMPOUNDS	NOT SPECIFIED
FORMALDEHYDE	50-00-0
BENZENE	71-43-2

WARNING:
THE FOLLOWING INGREDIENTS PRESENT IN THE PRODUCT ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS, OR OTHER REPRODUCTIVE HAZARDS.

CHEMICAL NAME	CAS NUMBER
TOLUENE	108-88-3
ARSENIC COMPOUNDS	NOT SPECIFIED
LEAD COMPOUNDS	NOT SPECIFIED
MERCURY COMPOUNDS	NOT SPECIFIED
CADMIUM COMPOUNDS	NOT SPECIFIED
BENZENE	71-43-2

INTERNATIONAL REGULATIONS: AS FOLLOWS

CANADIAN WHMIS:
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:
AB5
D2A
D2B

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:

HEALTH 2*
FLAMMABILITY 4
REACTIVITY 0
PERSONAL PROTECTION X

VOLATILE ORGANIC COMPOUNDS, G/L: 638 MAX

REASON FOR REVISION:

LEGEND:

- NOT APPLICABLE
- NOT ESTABLISHED
- NOT DETERMINED

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.