

**MATERIAL SAFETY DATA SHEET**

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

<b>Product:</b>	SBF-12, SBF-12BK, SBF-12CQ, SBF-17 SBF-17CQ, SBF-17BK, SBF-18, SBF-18BK	<b>Trade Name:</b>	Silicone Brake Fluid
<b>Manufacturer:</b>	AGS Company	<b>Common Name:</b>	DOT 5 Brake Fluid
<b>Street Address:</b>	2651 Hoyt St		
<b>City/State/Zip</b>	Muskegon Hts., MI 49444		
<b>Phone:</b>	800-253-0403	<b>Original Issue Date:</b>	10/8/1993
<b>Phone:</b>	231-733-2101	<b>Revision No</b>	8
<b>FAX:</b>	231-733-1784	<b>Date</b>	1/18/2010
<b>Transportation Emergency:</b>	CHEM-TEL		
<b>Phone:</b>	800-255-3924		

**SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS**

ITEM		CAS NUMBER	WT/WT %
	1 Tributyl Phosphate	126-73-8	1-5

**EXPOSURE LIMITS**

ITEM	TLV-TWA	ACGIH	TLV-STEL	OSHA	PEL-TWA	PEL-CEILING
1		2 mg/m <sup>3</sup>		5 mg/m <sup>3</sup>		30 ppm IDLH

(See Section 16 for abbreviation legend)

**SECTION 3 - HAZARDS IDENTIFICATION**

**EYE CONTACT:** May be irritating and can cause pain, tearing, reddening and swelling.

**SKIN CONTACT:** Prolonged contact may result in irritation.

**INHALATION:** May cause irritation to the mucous membranes.

**INGESTION:** This material may be harmful if swallowed.

**CHRONIC HAZARDS:** Prolong inhalation of vapors can cause general poisoning and paralysis.

Primary Route(s) of Entry Skin and eye contact or ingestion and inhalation.

**SECTION 4 - FIRST AID MEASURES**

**EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists

**SKIN CONTACT:** Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**INGESTION:** Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**SECTION 5 - FIRE FIGHTING MEASURES**

<b>FLASH POINT:</b>	408°F	<b>LOWER EXPLOSIVE LIMIT:</b>	N.D.	%
		<b>UPPER EXPLOSIVE LIMIT:</b>	N.D.	%
<b>AUTOIGNITION TEMPERATURE:</b>	N.D.			
<b>EXTINGUISHING MEDIA:</b>	CO <sub>2</sub> , Dry Chemical, Foam			

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Product can produce dense smoke from oils burning.

**MATERIAL SAFETY DATA SHEET**

SPECIAL FIREFIGHTING PROCEDURES: Wear NIOSH/MSHA approved self-contained breathing apparatus and protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

RECOVERY PROCEDURES: Absorb with an inert material and place in a chemical waste container.

**SECTION 7 - HANDLING AND STORAGE**

HANDLING: Wash thoroughly after handling

STORAGE: Store in cool dry environment.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

ENGINEERING CONTROLS: General exhaust to maintain concentration below the PEL.

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed, however, if high vapor concentration should develop, use a NIOSH approved organic vapor respirator.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves.

EYE PROTECTION: Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Eye wash in work area.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

BOILING RANGE	N.A.	VAPOR DENSITY:	Is heavier than air
ODOR	Odorless	ODOR THRESHOLD	N.D.
APPEARANCE	Purple Color	EVAPORATION RATE	Is slower than Butyl Acetate
SOLUBILITY IN H <sub>2</sub> O	Insoluble		
POUR POINT	-67°F	SPECIFIC GRAVITY	0.958 at 25°C
VAPOR PRESSURE	< 0.1 mmHg @ 20°C	pH @ 0.0%	N.A.
PHYSICAL STATE	Liquid	VISCOSITY:	42-43 cs at 25°C
COEFFICIENT OF WATER / OIL DISTRIBUTION: Negligible			

**SECTION 10 - STABILITY AND REACTIVITY**

CONDITIONS TO AVOID: Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon, nitrogen, phosphorus and silica.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

**SECTION 11 - TOXICOLOGICAL PROPERTIES**

PRODUCT LD-50 1863 mg/kg PRODUCT LC-50 123 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME	LD50	LC50
Dimethylpolysiloxane	20000 mg/kg/rat	N.E.
Tributyl Phosphate	1863 mg/kg/adult hen	123 ppm/6 hr/rat

**MATERIAL SAFETY DATA SHEET****SECTION 12 - ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION: LC50 Carp >10,000 mg/l/72 hr /Conditions of bioassay not specified

**SECTION 13 - DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION INFORMATION**

DOT PROPER SHIPPING NAME Not regulated

DOT TECHNICAL NAME

DOT HAZARD CLASS HAZARD SUBCLASS:

DOT UN / NA NUMBER: PACKING GROUP: NA RESP. GUIDE PAGE

**SECTION 15 - REGULATORY INFORMATION**

U.S FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 cfr 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III ) and is considered, under applicable definitions, to meet the following categories:

Acute health hazard

SARA SECTION 313

This product contains the following substance subject to the reporting requirements of Section 313 of Title of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT /WT % IS LESS THAN
No SARA Section 313 components exist in this product		%

TOXIC SUBSTANCE CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
Dimethylpolysiloxane	63148-62-9
Tributyl Phosphate	126-73-8

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Dimethylpolysiloxane	63148-62-9

PENNSYLVANIA RIGHT-TO-Know

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
Dimethylpolysiloxane	63148-62-9

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are know to the state of California to causes cancer, birth defects or other reproductive harm.

**MATERIAL SAFETY DATA SHEET**

CHEMICAL NAME

CAS NUMBER

No Proposition 65 chemicals exist in this product

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

**SECTION 16 - OTHER INFORMATION**

HMIS RATINGS:	Health	2	Flammability	1	Phys. Haz.	0	PPE	A
NFPA	Health	2	Flammability	1	Reactivity	0		

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.00 lbs / gal 0 grams / liter

LEGEND:	N.A.	Not Applicable	N.E.	Not Established
	N.D.	Not Determined		