Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

HMIS®

HEALTH 3 REACTIVITY

0

FLAMMABILITY

3 PERSONAL PROTECTION

A

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
Emergency Telephone Number 1-800-535-5053
Telephone Number for Information 1-913-397-9889
Date Prepared May 1, 2002
Signature of Preparer (Optional) Regulatory Dept.

SECTION II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific				OTHER LIMITS RECOMMENDED	
Chemical Identity; Common Name(s))	CAS No.	OSHA PEL	ACGIH TLV		% (Opt.)
Isobutane	75-28-5	800 ppm	800 ppm		15 - 40 %
Propane	74-98-6	1000 ppm	Asphyxiant		30 - 60 %

This product is not known to contain any chemical listed or in concentrations requiring reporting under SARA Title III Sec. 313. Refer to 40 CFR 372.

TSCA: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

Any substance listed as hazardous by the States of California, Florida, Illinois, Michigan, New Jersey, Ohio, Pennsylvania or Texas is described above if known present in regulated concentrations.

SECTION III Physical/Chemical

Characteristics

Boiling Point		Specific Gravity $(H_2O = 1)$	
Concentrate	Concentrate	0.57	
Pressure (psig. @ 70° F)		Melting Point	
	100 ± 5		No Data
Vapor Density (AIR = 1)	Greater that	Evaporation Rate (Butyl Acetate = 1)	
	one (1)		No Data
Solubility in Water		рН	Not
Slight			Applicable
Appearance and Odor - Clear colorless odorless	s gas in an aerosol	VOC'sThis product contains 351.5 grams per live weight VOC's.	ter or 100% by
can.		weight vocs.	

SECTION IV - Fire and Explosion Hazard Data

USA Flame Projection Test (ASTM D-3065)	Flammable Limits	LEL	UEL
Greater than 24", Flashback: Extremely flammable	No Data	No Data	No Data

Extinguishing Media -

Use water spray to keep containers cool. Contains an extremely flammable gas.

Special Fire Fighting Procedures - Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear self-contained breathing apparatus in chemical fires.

Unusual Fire and Explosion Hazards - Aerosol container (pressurized) may burst if heated over 120° F. Extremely flammable contents. Vapors are heavier than air and may accumulate in low lying areas. Vapors are easily ignited by pilot lights, flame, sparks, static electricity, electrical motors, switches, etc.

08412	12 May 1, 2002									
SECTION V	- React	ivity Data								
Stability	Uns	stable		Conditions to Avoid - Extreme heat, direct sunlight, ignition sources				ignition sources		
v	Sta	ble	X				,			
Incompatibility	(Mater	rials to Avoid	l) -							
Strong oxidizers			,							
Hazardous Dec	omposit	ion or Bypro	ducts -							
Oxides of carbon	•									
Hazardous	May	Occur		Conditions to Avoid - None known						
Polymerizatio	n Will	l Not Occur	X	10000 100000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 100000 10000 100000 10000 10000 10000 10000 10000 10000 100000 100						
SECTION VI	- Healtl	h Hazard Data								
Route(s) of En	try	Eyes?		Inhalation	?		Skin?		Ingestion?	
		Yes		Yes			Yes		No (unlikely)	
Health Hazards	(Acute	and Chronic)	-							
							e or thermal type). M			
	rd due to	potential for dis	placing ox	ygen. Follow	good chem	nical	hygiene practices to	avoid t	these hazards. Contents	
under pressure.		NEDO			TARG	3.7	1.0	OCII	A D 1 / 10	
Carcinogenici None k	-	NTP?	No		IARC	MOI	nographs? No	USH	A Regulated? No	
Signs and Sym			INU				INU		INO	
-	_	-	es. Disorie	entation, lack o	f coordina	tion.	excitation, headache	nause	a if inhaled.	
Medical Condit							onenanon, neadaone	, masse	w 11 1111wive	
						al hy	giene practices to avo	oid this	hazard.	
Emergency and				<u> </u>						
•				tes lifting eyeli	ds to insur	re co	mplete removal. Ge	t imme	ediate medical attention.	
							nhalation - Get to fr			
stopped, qualified	personne	el should adminis	ter artificia	al respiration.	Skin - Flu	ish o	r immerse area(s) in	lukewa	rm water. If skin is not	
burned or frozen, l	keep wari	m and stimulate c	irculation	with massage.	Get medic	al at	tention.			
SECTION VI	I - Pre	cautions for Sa	fe Handl	ing and Use						
Steps to be Take	en in Ca	ase Material is	Released	or Spilled - I	Danger, ex	ktren	nely flammable gas.	Isola	ate traffic and ventilate	
area. Eliminate al	l ignition	sources. Wear p	protective g	gear as necessar	ry. Dike to	o pre	event spread.			
Waste Disposal Method - Consult local, state and federal regulations. Do not puncture or incinerate container. Replace										
cap on empty can, wrap, then discard container if allowed by applicable statutes.										
Precautions to be Taken in Handling and Storing - Do not use near ignition sources such as heat, sparks, open flame, etc.										
Direct spray away from face. Replace cap when not in use. Do not get in eyes, on skin or clothing. Do not smoke while using. Use with										
adequate ventilation.										
Other Precautions - Follow label directions carefully. Keep out of reach of children. Do not deliberately concentrate and inhale vapors. Store in a cool (under 120° F) dry location away from heat, sparks, open flame and direct sunlight.										
inhale vapors. Sto	re in a co	ool (under 120° F) dry locat	ion away from	heat, spark	ks, o	pen flame and direct	sunligh	t.	
SECTION VI	II - Co	ntrol Measures								
					Use with	adec	quate ventilation. If	PELs	or TLVs are	
exceeded (see Section II), use an approved NIOSH\MSHA respirator. Nontiletion Legal Enhance None Non										
Ventilation		Exhaust			-		ecial		None	
		nical (General) -	Acceptable		Oth			None	
Protective Gloves Eye Protection										
Only if direct contact possible. Only if direct contact possible.										
Other Protective	e Cloth	ning or Equip	ment							

Not usually necessary. If direct contact possible, wear apron, boots, face shield, gloves, etc.

Work/Hygienic Practices -

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc.

NARNING! The use of this product is beyond the counts of the manufacture; herefore, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The user must assume all responsibility, including injury or damage, resulting from its missues as such, or in combination with other materials.

The manufacture warrants only that this product meets the manufacture's specifications for such product. THIS WARRANTY ISIN ILLIED AS TO DESCRIPTION, QUALITY, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, PRODUCTIVENESS, OR ANY OTHER MATTER, OF THIS PRODUCT. THE MANUFACTURER SHALL BE IN NO WAY RESPONSIBLE FOR THE IMPROPER USE OF THIS PRODUCT. The sole and exclasive remody against the manufacturer for breach of warranty shall be reimburnement of the purchase price of the product in the event that a defective condition of the product in the event that affective condition of the product in the event that affective condition of the product remove of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the product in the event that affective condition of the event that affective cond