Material Safety Data Sheet



SAN MAX

Section 1. Chemical product and company identification

Trade name	: SAN MAX
Product use	: Sanitizer.
Supplier	: Ecolab Inc. Institutional Division
	370 N. Wabasha Street
	St. Paul, MN 55102
	1-800-352-5326
Code	: 918599
Date of issue	: 12-August-2005
EPA Registration No.	: 47371-180-1677
	EMERGENCY HEALTH INFORMATION: 1-800-328-0026
	Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, Information on Ingredients

Name	<u>CAS number</u>	<u>% by weight</u>
didecyldimethylammonium chloride	7173-51-5	5 - 20
quaternary ammonium compounds, benzyl-c12-c16-alkyldimethyl, chlorides	68424-85-1	5 - 20
ethanol	64-17-5	1 - 5

Section 3. Hazards identification

Physical state	: Liquid. (Liquid.)	
Emergency	: DANGER!	
overview		
	CAUSES EYE AND SKIN BURNS.	
	COMBUSTIBLE LIQUID AND VAPOR.	
	VAPOR MAY CAUSE FLASH FIRE.	
	MAY BE FATAL IF ABSORBED THROUGH SKIN OR IF SWALLOWED.	
	HARMFUL IF SWALLOWED.	
	Do not ingest. Do not get in eyes, on skin or clothing. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate	
	ventilation. Wash thoroughly after handling.	
Potential acute heal	0, 0	
Eyes	: Corrosive to eyes.	
Skin	: Corrosive to the skin.	
Inhalation	: Slightly irritating to the respiratory system.	
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.	
See toxicological Information (section 11)		

Section 4. First aid measures

Eye contact	 In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
Inhalation	: If inhaled, remove to fresh air.
Ingestion	: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire fighting measures

Products of combustion :	59.4444 °C (Closed cup) These products are halogenated compounds, hydrogen chloride. In case of fire, use water spray (fog), foam, dry chemicals, or CO $_2$.
Special protective equipment : for fire-fighters	Dike area of fire to prevent product run-off. Combustible liquid and vapor. Vapor may cause flash fire. Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure

Section 6. Accidental release measures

Personal precautions	: Immediately contact emergency personnel. Eliminate all ignition sources. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Do not touch or walk through spilled material.
Environmental precautions	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for cleaning up	: If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal

Section 7. Handling and storage

Handling Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Avoid breathing vapor or mist. Keep away from heat, sparks and flame. To avoid fire, minimize ignition sources. Wash thoroughly after handling. Storage Keep out of the reach of children. Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid

all possible sources of ignition (spark or flame). Do not store above 50°C

Section 8. Exposure Controls, Personal Protection

Engineering controls	: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations or vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Personal protecti	, ,
Eyes	: Use chemical splash goggles. For continued or severe exposure wear a face shield over the
	goggles.
Hands	: Use chemical resistant, impervious gloves.
Skin	: Wear suitable protective clothing.
Respiratory	: No protective equipment is needed under normal use conditions.
Name	Exposure limits
ethanol	ACGIH TLV (United States, 1/2004). Notes: 1996 Adoption Refers to
	Appendix A Carcinogens.
	TWA: 1880 mg/m ³ 8 hour(s). Form: All forms
	TWA: 1000 ppm 8 hour(s). Form: All forms
	OSHA PEL (United States, 8/1997).
	TWA: 1900 mg/m ³ 8 hour(s). Form: All forms
	TWA: 1000 ppm 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

Physical state Color	: Liquid. (Liquid.) : Blue.
Odor	: Sweetish.
рН	: 7 (100%)
Specific gravity	: 0.987 (Water = 1)

Section 10. Stability and reactivity

Stability: The product is stable.Hazardous decomposition: These products are halogenated compounds, hydrogen chloride.products

Section 11. Toxicological information

Potential acute health effects

Eyes	: Corrosive to eyes.
Skin	: Corrosive to the skin.
Inhalation	: Slightly irritating to the respiratory system.
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.
Chronic effects on humans	 Contains material which causes damage to the following organs: blood, the reproductive system, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

Products of degradation	These products are carbon oxides (CO, CO ₂) and water, nitrogen oxides (NO, NO ₂	
), halogenated compounds. Some metallic oxides.	

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Waste : Unused product is D001 (Ignitable)

classification

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	Not regulated.	-	-	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification	: Combustible liquid Corrosive material Target organ effects
U.S. Federal regulations	: SARA 302/304/311/312 extremely hazardous substances: None. SARA 302/304 emergency planning and notification: None.
TSCA 8(b) inventory California prop. 65	 All materials are listed or exempt. No products were found.

EPA Registration No.

: 47371-180-1677

Section 16. Other information

Hazardous Material Information System (U.S.A.)	:	Health	3
		Fire hazard	2
		Reactivity	0
		Personal protection	В
Date of issue	:	12-August-2005.	
Responsible name	:	Regulatory Affairs	
Date of previous issue	:	12-August-2005.	
Notice to reader		U U	

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.