

MATERIAL SAFETY DATA SHEET

Page 1 of 1
 Revised 5/25/99
 Replaces 4/27/99
 Printed 7/26/99

QUICKSEAL THREADSEAL 40Z BRTOP

MSDS ID: 32577

Premier Farnell Corp.
 4500 Euclid Avenue
 Cleveland, Ohio 44103

Emergency/Information Telephone:
 216-391-8300

(In Canada)
 Premier Fastener Ltd.
 271 Attwell Drive
 Etobicoke, Ontario M9W 5B9

Formula: JC30 TSC
 MSDS Effective: 02/13/97

Section I - Product Identification

Part Number: 32577
 Product Name: QUICKSEAL THREADSEAL 40Z BRTOP
 Trade Name/Synonyms: QUICK SEAL
 Chemical Family: SEALANT

Section II - Hazardous Ingredients

Ingredient	CAS No.	WT %	Pel	TLV	Stel	Units	LC50, PPM	LD50, MG/KG
POLYTETRA FLUORO-ETHYLENE (TFE) AS THERMAL	09002-84-0	30-50	N/A	N/A	N/A		N/A	N/A
PETROLEUM GREASE	MIXTU-RE-	15-40	N/A	N/A	N/A		N/A	N/A
PETROLEUM OIL	MIXTU-RE-	10-30	N/A	N/A	N/A		N/A	N/A
INHIBITORS	T.SEC-RE-T	1-5	N/A	N/A	N/A		N/A	N/A

Section III - Physical Data

Boiling Pt Deg F/C: N/A
 Vapor Pressure(MM HG):N/A
 Vapor Density(Air=1):HEAVIER THAN AIR
 Solubility In Water: NEGLIGIBLE
 Physical State: PASTE
 Freeze PT Deg F/C: N/A
 Appearance And Odor: WHITE GRANULAR PASTE
 Voc:Lbs/Gal=N/A ; Grams/Liter=N/A ; Grams Voc/Gram Solid=N/A ; % Voc N/A

Specific Gravity:1.3
 %Volatile Volume:N/A
 Evaporation Rate:N/A
 Water/Oil Dist Coeff:0
 PH: N/A
 Threshold Odor,PPM: N/A

Section IV - Fire and Explosion Hazard Data

Classification: N/A
 Combustion Products: CO, CO2, HF, FLUORIDES
 Flash Point Deg F/C: 350 F / 177 C
 Extinguishing Media: FOAM, CO2, DRY CHEMICAL
 Auto Ign. Temp Deg F/C: N/A
 Special Fire Fighting Procedures:
 FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING EQUIPMENT.
 Unusual Fire And Explosion Hazards:
 CONTACT WITH FLAME OR HOT SURFACES MAY PRODUCE TOXIC GASES.

NFPA Rating: 1,1,0 HMIS: 1,1,0
 Lcl%:N/A Uel%:N/A

MATERIAL SAFETY DATA SHEET

Page	3 of
Revised	5/25/99
Replaces	4/27/99
Printed	7/26/99

QUICKSEAL THREADSEAL 4OZ BRTOP

MSDS ID: 32577

Section IX - Special Precautions (Cont.)

PHYSICIAN IMMEDIATELY, SHOW LABEL OR MSDS.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. ALWAYS READ & FOLLOW DIRECTIONS ON PRODUCT LABEL. ADDITIONAL TECHNICAL DATA SHEETS AND/OR MATERIAL SAFETY DATA SHEETS (MSDS) ARE AVAILABLE UPON REQUEST. FOR PROFESSIONAL & INDUSTRIAL USE ONLY.

Symbols, Abbreviations and Notations:

#=Listed in SARA Title III Section 313; @=Non-hazardous ingredient among the 5 most predominant substances; +=Contains encapsulated Silica-Crystalline or Carbon Black.

Normal product usage should not result in respirable dust that would be hazardous to the respiratory system; N/A-Not available or applicable; *=If found as dust, mist or fume; C=Ceiling limit; S=Skin designation; M=Human; RAB=Rabbits; GPG=Guinea Pigs; MIC=Mice; I=Ingestion; A=Skin absorption; LO=Little observable effect; NO=No effect; Pel=OSHA permissible exposure limit; TLV=ACGIH threshold limit value; Stel=Short term exposure limit.

All components of this product are listed or are exempt from listing on the TSCA inventory and/or the Canadian DSL or NDSL. MSDS prepared by the Corporate Compliance department.

The information and recommendations provided herein are believed to be correct as of the date hereof. However, such information and recommendations are provided without warranty of any kind and Premier Farnell Corp. disclaims any and all liability or legal responsibility for use or reliance upon same.