

1696 West Grand Avenue, Oakland, CA 94607-1607 Tel (510) 839-1000 - Fax (510) 839-1090

Commercial and Industrial Water Treatment Programs Since 1927

Product Information:

Trade Name (as labeled):	SKASOL 91-L
Manufacturer's Name:	Skasol Incorporated
Address (complete mailing address):	1696 West Grand Avenue
	Oakland, California 94607-1607
24 Hour Emergency Telephone:	(800) 424-9300
Information Telephone:	(510) 839-1000
Date prepared or revised:	May 11, 2006
Name of preparer:	Michelle Navasca

Hazardous Ingredients:

Chemical Name	CAS Number	Percent	Limits in Air	(give units)	
			ACGIH TLV	OSHA PEL	Other (specify)
Sodium Hydroxide	1310-73-2	< 3.5%	2mg/m ³	2mg/m³	Ceiling

Physical Properties:

1 113010011 1 100011					
Vapor Density:	Not available	Melting Point or Range:	Not applicable		
Specific Gravity:	1.10	Boiling Point or Range, °F:	218		
Solubility in Water:	Complete	Evaporation Rate:	Not available		
Vapor pressure:	Not available				
Appearance and Odor:		Clear liquid, organic odor.			
How to detect this substan	ce:	Sodium Hydroxide may cause irritation on contact.			

Fire and Explosion:

1	Flack and the OF (since mostle ed).	None
- 1	Flash point, °F (give method):	140116
	Auto ignition temperature, °F:	None

Flammable limits in air, volume %:	None	lower (LEL)	upper (UEL)	

Fire extinguishing materials:

The extinguishing materials.									
Water	Х	Foam	X	CO ₂	X	Dry Chemical	X	Other	
Special fire	Special fire fighting procedures: Wear full protective clothing and respiratory protection.								
Unusual fire and explosion hazards: None.									

Health Hazard Information:

Symptoms of overexposure for each potential route of exposure.

Symptoms of overexposure	e for each potential route of exposure.
Inhaled:	Mist or liquid may cause some minor irritation of the respiratory tract.
Contact with skin or eyes:	Causes severe burning to eyes. Skin is more resistant, but prolonged exposure can cause irritation.
Absorbed through skin:	Not absorbed.
Swallowed:	Will cause burning damage to mouth, esophagus, stomach, etc.



Health Hazard	1
Fire Hazard	0
Reactivity Hazard	0
Specific Hazard	2

1696 West Grand Avenue, Oakland, CA 94607-1607 Tel (510) 839-1000 - Fax (510) 839-1090

Commercial and Industrial Water Treatment Programs Since 1927

Health Hazard Information (continued):

Heath effects or risks from exposure:

Acute:	None
Chronic:	None

First Aid Emergency Procedures:

I II St Ald Ell	lergency i roccaures.
Eye Contact:	Immediately flush with plenty of water, raising eyelids often to help irrigation and continue for at least 15 minutes. Get
,	medical assistance.
Skin Contact:	Flush with plenty of water. Remove contaminated clothing. If skin is slippery alkalinity is still present. Continue rinsing until
	slipperiness is gone.
Inhaled:	Remove to fresh air. If not breathing give artificial respiration (preferably mouth to mouth). Call a physician or poison
	control center.
Swallowed:	If conscious drink large quantities of water or milk. Do not induce vomiting. Get medical attention. Never give anything by
	mouth to an unconscious person.

Suspected cancer agent?

Х	X No: This product's ingredients are not found in the lists below.				
	Federal OSHA	National Toxicology Program	International Assoc. For Research On Cancer		
	1 000101	3, 3			

Medical Conditions Aggravated By Exposure	Not Know
-------------------------------------------	----------

Reactivity Data:

Stability:

- tability .				
X	Stable	U	nstable	
Conditions to	o avoid:		Do not mix with strong acids	5.
Incompatibili	ty (materials to avoid):		Strong acids .	

Hazardous decomposition products:	Oxides of sulfur, heat.			
Hazardous polymerization:	May occur	Х	Will not occur	

Conditions to avoid:	Not known

Spill, Leak and Disposal Procedures:

Spill, Leak and Disposar Frocedures.	
Spill response procedures:	Dike area to contain the spill. Small spills may be flushed and diluted with lots of water and washed to
	a sewer connected to a waste treatment plant.
	Larger spills should be contained and neutralized with dilute acid to a neutral pH (6.0-9.0) before washing with plenty of water to a sewer connected to a waste treatment plant. Any DOT container is
	suitable for temporarily holding neutralized waste.

Special Handling Information:

Special nandling information.	
Ventilation and Engineering Controls:	Local exhaust ventilation should be sufficient to minimize employee exposure excessive mist.
Respiratory Protection:	When conditions require it, use a respirator approved by NIOSH/MSHA with a dust/mist filter. Respiratory protection programs must meet or exceed the requirements of Title 29 CFR
	1910.134
Eye Protection:	Close fitting chemical safety goggles with a face shield if needed.
Gloves:	Nitrile, neoprene or natural rubber.
Other Clothing and equipment:	Rubber boots with safety toes, rubber aprons, plastic hard hats should be used when necessary to prevent skin contact.
Work practices, hygienic practices:	Protective clothing and use of equipment must be in accordance with Title 29 CFR Sections 1910.132 and 1910.133
Other Handling and Storage Needs:	Provide emergency eye wash stations and emergency shower facilities near use and handling areas.
Measures during Maintenance:	Chemical feed pumps should be routinely washed out with water. Plastic tubing and fittings should be frequently inspected for leaks and clogs. As with all automatic equipment, be certain that the power is disconnected before performing any adjustments or repairs. Use all above precautions.
Disclaimer:	All information, recommendations and suggestions appearing in this MSDS concerning the use of our products are based upon tests and data believed to be reliable. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals reading this information must exercise their independent judgment when determining its appropriateness for a particular purpose.