

02-200 ✓ 02-205

— — — MASCO PAINT MFG. INC. 671 BERGIN WAY SPARKS NV. (702) 359-9161 — — —

#900B 100% ACRYLIC ENAMEL SEMI-GLOSS

GENERAL INFORMATION

Description: A premium quality 100% acrylic semi gloss enamel with excellent durability and scrubability. It combines excellent coverage with ease of application for a quality finish coat.

Recommended Usage: For interior and exterior use on wood, metal, masonry, trim, patios, decks and porches.

Surface Preparation: All surfaces should be clean, dry, free of wax, grease, excess alkalinity, oil, chalk and loose or peeling paint. Efflorescence (salt like deposits) must be removed before painting by washing with a mild muriatic acid solution, followed by a good rinse with clear water (avoid contact with eyes and skin). Allow to dry thoroughly. Glossy surfaces must be sanded and dusted clean.

Application: Stir well before using. Apply with brush, roller or spray. Apply only when the temperature of the surface, air and material is above 50°F. Do not apply if rain is expected within 24 hours.

Coverage: Approximately 200-400 square feet per gallon depending on surface texture and porosity.

Drying Time: Dries to touch in 4 hours depending on the temperature and humidity.

Thinning: None recommended. If necessary, add no more than ½ pint of water per gallon. Do not use paint thinner.

Clean-Up: Clean brushes, rollers and equipment with soap and water.

Sheen: Semi Gloss Enamel

Container Sizes: Available in quarts, gallons and fives.

SPECIFICATIONS

Weight per gallon: 10.5 lbs

Film Thickness: Dry-1 to 2 mils

Gloss: 60° to 80°

Solids: 48% by Weight 34.2% by Volume

Analysis: Pigment 24.4% Vehicle 75.6%

Viscosity: 85 to 90 KU.

VOC: Less than 250 Grams per Liter

FEDERAL SPECS: TTP-1511

MATERIAL SAFETY DATA SHEET

P: 1

PRODUCT NAME: INT/EXT 100% ACRYLIC ENAMEL SEMI GLOSS
PRODUCT CODE: MASCO #900B

HMS CODES:

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: MASCO PAINT MFG. INC.
ADDRESS: 671 BERGIN WAY SPARKS, NEVADA 89431

EMERGENCY PHONE: (702)359-9161
INFORMATION PHONE: (702)359-9161

DATE PRINTED: 05/10/95
NAME OF PREPARER:

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
PROPYLENE GLYCOL ACGIH TLV: NOT ESTAB.	57-55-6	.1	68	3
ESTER ALCOHOL ACGIH TLV: NOT ESTAB.	25265-77-4	.013	77 F	2

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 369 deg F - 471 deg F	SPECIFIC GRAVITY (H2O=1): 1.19
VAPOR DENSITY: Lighter than air.	EVAPORATION RATE: Slower than ether
COATING V.O.C.: 1.37 lb/gl	MATERIAL V.O.C.: 0.47 lb/gl
SOLUBILITY IN WATER: Complete.	
APPEARANCE AND ODOR: Typical for water based paints.	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 214 deg F **METHOD USED:** TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .62 **UPPER:** 12.5

EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical, or Water Fog.

SPECIAL FIREFIGHTING PROCEDURES
Cool containers with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Closed container exposed to high temperatures may explode or burst due to build up of steam pressure.

SECTION V - REACTIVITY DATA

STABILITY: Stable.
CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)
Avoid contact with strong oxidizing agents.

MATERIAL SAFETY DATA SHEET
INT/EXT VINYL ACRYLIC SEMI-GLOSS

Page:

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

toxic materials; Carbon Dioxide, Carbon Monoxide, Various Hydrocarbons, etc. on thermal decomposition.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYES: In direct contact, may cause irritation. **SKIN:** Prolonged and repeated contact with product may cause skin irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: May cause irritation to skin, eyes, and intestinal system. **CHRONIC:** Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage.

CARCINOGENICITY: NTP CARCINOGEN: No **IARC MONOGRAPHS:** No **OSHA REGULATED:** No

WARNING! THIS PRODUCT IS KNOWN TO CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, AND/OR OTHER REPRODUCTIVE HARM. (CALIF. HEALTH AND SAFETY CODE SECTION 25249.5)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

None known.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with large amounts of water for at least 15 Minutes. Take to a physician. **SKIN:** Wash affected areas with soap and water. Remove contaminated clothing. If irritation persists, consult physician. **INHALATION:** Remove to fresh air. Treat symptomatically. Consult physician. **INGESTION:** Drink 1 or 2 glasses of water to dilute. **DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.**

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike, contain, or absorb with inert materials. Transfer to containers for recovery or disposal. Prevent runoff into sewers, streams, or other bodies of water.

WASTE DISPOSAL METHOD

Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not expose to extremes in temperature. Avoid exposure to high temperatures. **DO NOT ALLOW TO FREEZE.**

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. Avoid prolonged or repeated exposure to levels above TLV. **KEEP OUT OF REACH OF CHILDREN.**

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

Not normally required. If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self-contained breathing

MATERIAL SAFETY DATA SHEET
INT/EXT VINYL ACRYLIC SEMI-GLOSS

Page:

atus.

VENTILATION

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES

Wear resistant gloves such as polyethylene.

EYE PROTECTION

Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear impervious clothing. Eyewash station.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using restrooms. Remove and wash all contaminated clothing before reuse.

SECTION IX - DISCLAIMER

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.