Commercial and Industrial Water Treatment Programs Since 1927

Product Information:

Trade Name (as labeled):	SKASOL 5379-S
Manufacturer's Name:	Skasol Incorporated
Address (complete mailing address):	1696 West Grand Avenue
	Oakland, California 94607-1607
24 Hour Emergency Telephone:	(800) 424-9300
Information Telephone:	(510) 839-1000
Date prepared or revised:	March 24, 2006
Name of preparer:	Michelle Navasca

Hazardous Ingredients:

Chemical Name	CAS Number	Percent	Limits in Air ACGIH TLV	(give units) OSHA PEL	Other (specify)
Sodium Hydroxide	1310-73-2	< 5%	2mg/m³	2mg/m³	Ceiling
				iii	

Physical Properties:

Vapor Density:	Not available	Melting Point or Range:	Not applicable
Specific Gravity: 1.10		Boiling Point or Range, °F:	218
Solubility in Water: Complete		Evaporation Rate:	Not available
Vapor pressure: Not available			
Appearance and Odor:		Clear liquid, organic odor.	
How to detect this substance:		Sodium Hydroxide may cause irrit	tation with any contact.

Fire and Explosion:

Flash point, °F (give method):	None
Auto ignition temperature, °F:	None

Flammable limits in air, volume %:	None Low	er (LEL)	Upper (UEL)	

Fire extinguishing materials:

Water	Х	Foam	Х	CO ₂	Х	Dry Chemical	Х	Other	
Special fire fighting procedures: Wear full protect			rotective cloth	ing and respi	iratory protection.				
Unusual fire and explosion hazards: None.									

Health Hazard Information:

Symptoms of overexposure for each potential route of exposure.

Inhaled:	Mist or liquid will cause some minor irritation of the respiratory tract. Large amount will cause burning from
	caustic contents.
Contact with skin or eyes:	Causes severe burning to eyes. Skin is more resistant, but prolonged exposure can cause irritation.
Absorbed through skin:	Not absorbed.
Swallowed:	Will cause burning damage to mouth, esophagus, stomach, etc.

HEALTH HAZARD	_
4. Deadly	
3. Extreme Hazard	
2. Hazardous	
1. Slightly Hazardou	s red
0. Normal Material	blue
SPECIFIC HAZARD	Name of the second
 Oxidizer 	while
3. Acid	\ , \
2. Alkali	/
1. Corrosive	*
0. Use no water	

FIRE HAZARD

- FIRE HAZARD

 4. Below 73 degree F (Boiling pt. below 100 degree F)

 5. Below 73 degree F (Boiling pt. at/above 100 degree F and/or at/above 73 degree F not exceeding 100 degree F)

 2. Above 100 degree F not exceeding 200 degree F)

 1. Above 100 degree F

- 0. Will not burn

- REACTIVITY
 4. May detonate
 3. Shock and heat may detonate 2. Violent chemical change
 - Unstable if heated
 Stable

Health Hazard	2
Fire Hazard	0
Reactivity Hazard	0
Specific Hazard	2

1696 West Grand Avenue, Oakland, CA 94607-1607 Tel (510) 839-1000 - Fax (510) 839-1090

Commercial and Industrial Water Treatment Programs Since 1927

Health Hazard Information (continued):

Heath effects or risks from exposure:

Acute	Sodium Hydroxide will cause burns with acute exposure.		
Chronic	Same as acute, but with milder symptoms		

First Aid Emergency Procedures:

	organity i recodulities				
Eye Contact	Immediately flush with plenty of water, raising eyelids often to help irrigation and continue for at least 15 minutes.				
	Get medical assistance.				
Skin Contact	Flush with plenty of water. Remove contaminated clothing. If skin is slippery alkalinity is still present. Continue rinsing				
	until slipperiness is gone.				
Inhaled	Remove to fresh air. If not breathing give artificial respiration (preferably mouth to mouth). Call a physician or poison				
	control center.				
Swallowed	If conscious drink large quantities of water, milk or sodium bicarbonate. Do not induce vomiting. Get medical attention.				
	Never give anything by mouth to an unconscious person.				

Suspected cancer agent?

	X No: this product's ingredients are not found in the lists below.				
Federal OSHA National Toxicology Program International Assoc. For Research On Co.				International Assoc. For Research On Cancer	

Medical Conditions Aggravated By Exposure	Not Known	

Reactivity Data:

Х	Stable	Unstable			
Conditions	to avoid:	Do not i	nix with strong acids		
Incompatibility (materials to avoid):		Strong a	Strong acids		
Hazardous decomposition products:		Oxides	Oxides of sulfur, heat		
Hazardous	s polymerization:		May occur	Тх	will not occur

Spill, Leak and Disposal Procedures:

opini, admirant dispersion in the contract of			
Spill response procedures:	Dike area to contain the spill. Small spills may be flushed and diluted with lots of water and		
	washed to a sewer connected to a waste treatment plant.		
Preparing wastes for disposal:	Larger spills should be contained and neutralized with dilute acid to a neutral pH (6.0-9.0) before		
	washing with plenty of water to a sewer connected to a waste treatment plant. Any DOT		
	container is suitable for temporarily holding neutralized waste.		

Special Handling Information:

Ventilation and Engineering Controls:	Local exhaust ventilation should be sufficient to minimize employee exposure excessive dust.		
Respiratory Protection:	When conditions require it, use a respirator approved by NIOSH/MSHA with a dust/mist filter. Respiratory protection programs must meet or exceed the requirements of Title 29 CFR 1910.134		
Eye Protection:	Close fitting chemical safety goggles with a face shield if needed.		
Gloves:	Nitrile, neoprene or natural rubber.		
Other Clothing and equipment	Rubber boots with safety toes, rubber aprons, plastic hard hats should be used when necessary to prevent skin contact.		
Work practices, hygienic practices:	Protective clothing and use of equipment must be in accordance with Title 29 CFR Sections 1910.132 and 1910.133		
Other Handling and Storage Needs:	Provide emergency eye wash stations and emergency shower facilities near use and handling areas.		
Measures during Maintenance:	Chemical feed pumps should be routinely washed out with water. Plastic tubing and fittings should be frequently inspected for leaks and clogs. As with all automatic equipment, be certain that the power is disconnected before performing any adjustments or repairs. Use all above precautions.		
Disclaimer:	All information, recommendations and suggestions appearing in this MSDS concerning the use of our products are based upon tests and data believed to be reliable. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals reading this information must exercise their independent judgment when determining its appropriateness for a particular purpose		