

# Section 1 - Identification of the Mixture and of the Company

## Product Identification

Primary Identifier(s) Used on the Label

Berryman B-12 CHEMTOOL CARBURETOR, CHOKE & THROTTLE BODY CLEANER, Berryman B-12 CHEMTOOL THROTTLE BODY, CARBURETOR & CHOKE CLEANER Product Synonym(s) blend "1AA-CA11"

Product Number(s) 0110C, 0113C, 0117C, 0120C, and 0152

# Relevant Identified Uses and Uses Advised Against

Recommended Uses carburetor, choke, and air-intake/throttle body cleaning Uses Advised Against not for use in some applications

## Manufacturer/Supplier Details

Berryman Products, Inc. 3800 E Randol Mill Rd Arlington, TX 76011 (800) 433-1704 (USA/Canada) (817) 640-2376 (international) www.BerrymanProducts.com

# Emergency 24-Hour Telephone Number(s) – InfoTrac, Inc.

(800) 535-5053 (USA/Canada) (352) 323-3500 (international)

# Section 2 - Hazards Identification

Classification of the Substance or Mixture (29 CFR 1910.1200) Physical Hazards Flammable Aerosol – Category 1 Health Hazards Skin Irritant – Category 2 Eye Irritant – Category 2A Developmental – Category 2 Specific Target Organ Toxicity - Single Exposure – Category 3 (respiratory tract irritant and narcotic effects) Specific Target Organ Toxicity - Repeated Exposure – Category 2 (blood/blood system, central nervous system) Environmental Hazard - Acute – Category 3

## Allocation of Label Elements

Chemical Identity

Berryman B-12 CHEMTOOL CARBURETOR, CHOKE & THROTTLE BODY CLEANER; Berryman B-12 CHEMTOOL THROTTLE BODY, CARBURETOR & CHOKE CLEANER Pictograms



<u>Signal Word</u> DANGER

#### Hazard Statements

H222 – Extremely flammable aerosol.

H229 – Pressurized container—may burst if heated.

H315 – Causes skin irritation.

H319 – Causes serious eye irritation.

H335 – May cause respiratory irritation.

H336 – May cause drowsiness or dizziness.

H361d – Suspected of damaging the unborn child.

H373 – May cause damage to blood/blood system and central nervous system through prolonged or repeated exposure.

H402 - Harmful to aquatic life.

# Prevention Precautionary Statements

P101 – Keep out of reach of children.

P102 – Read label before use.

P201 – Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

P211 – Do not spray on an open flame or other ignition source.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment. Special precautions may be necessary for non-conductive containers.

P241 – Use explosion-proof electrical, ventilation, and lighting equipment.

P242 – Use only non-sparking tools, such as brass or bronze.

P243 - Take precautionary measures against static discharge.

P251 – Do not pierce or burn, even after use.

P260 – Do not breathe fumes, gas, mist, vapor, or spray.

P264 – Wash thoroughly with soap and water after handling.

P270 – Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 – Avoid release to the environment.

P280 – Wear protective gloves, protective clothing, and eye or face protection.

#### Response Precautionary Statements

P312 – Call POISON CONTROL CENTER, hospital emergency room, or doctor if you feel unwell.

P314 – Get medical advice/attention if you feel unwell.

P321 - Specific treatment available in this document in "Section 4 - First Aid Measures."

P303/P361/P353 – IF ON SKIN (OR HAIR): Immediately take off all contaminated clothing. Rinse skin with soap and water or shower.

P304/P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305/P351/P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P308/P313 – If exposed or concerned, get medical advice/attention.

P332/P313 – If skin irritation occurs, get medical advice/attention.

P337/P313 - If eye irritation persists, get medical advice/attention.

P362/364 - Take off contaminated clothing and launder before reuse.

P370/P378 – In case of fire, use water spray, water fog, dry chemical, alcohol-resistant foam, or carbon dioxide to extinguish.

#### Storage Precautionary Statements

P405 – Store locked-up.

P403/P235 - Store in a well-ventilated place. Keep cool.

P410/P412 - Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

#### Disposal Precautionary Statements

P501 – Dispose of contents/container in accordance with local, regional, national, and international regulations, as applicable.

### Hazards Not Otherwise Classified

none known

#### Ingredients of unknown acute toxicity

none

# Section 3 – Composition/Information on Ingredients

| <u>Component</u> | <u>CAS RN</u> | <u>Weight</u> |
|------------------|---------------|---------------|
| Acetone          | 67-64-1       | 80-90%        |
| Toluene          | 108-88-3      | <10%          |
| 2-Butoxyethanol  | 111-76-2      | <10%          |
| Carbon Dioxide   | 124-38-9      | 3-6%          |

# Section 4 – First Aid Measures

#### Description of First Aid Measures

#### Ingestion

Drink 1-2 glasses of milk or water. Call poison control center, hospital emergency room, or doctor if you feel unwell.

### Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### Skin Contact

Immediately take off all contaminated clothing. Rinse skin with soap and water or shower.

#### Inhalation

Remove person to fresh air and keep comfortable. If experiencing respiratory symptoms or if breathing is difficult, administer oxygen and call poison control center, hospital emergency room, or doctor.

### Most Important Symptoms and Effects

#### Acute/Immediate

respiratory tract irritation; headache and lightheadedness; narcotic effects, including dizziness, drowsiness, and loss of coordination; nausea and vomiting

#### **Delayed**

drying, cracking, or defatting of the skin

#### Indications of Need for Immediate Medical Attention and Specific Treatment Required Indications of Need for Immediate Medical Attention

In the event of shortness of breath or difficulty breathing, seek immediate medical attention. Specific Treatment and Notes to Physician No additional information available

# Section 5 - Firefighting Measures

## Fire Extinguishing Media

Support for Combustion Product supports combustion. Suitable Extinguishing Media water fog, dry chemical, alcohol-resistant foam, or carbon dioxide Unsuitable Extinguishing Media water jet/spray (may cause product to float to surface and reignite)

## Special Hazards/Considerations

### **Combustion Products**

Combustion in the presence of air may yield unburned hydrocarbons, carbon monoxide, carbon dioxide, and organic oxygenates.

#### Special Protective Equipment and Precautions for Firefighters Special Protective Equipment

Firefighters should employ SCBA and full protective gear, including shield, as product is comprised of low-boiling, flammable solvents and may vent, rupture, or explode violently at elevated temperatures.

#### Precautions and Procedures

Pressurized container—may burst if heated. Highly flammable liquid and vapor. Vapors heavier than air. Remove product from area if safe to do so. Use water spray to cool nearby containers.

# Section 6 - Accidental Release Measures

### Personal and Environmental Precautions

### Personal Precautions

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Special precautions may be necessary for non-conductive containers. Use explosion-proof electrical, ventilation, and lighting equipment. Use only non-sparking tools, such as brass or bronze. Do not breathe fumes, gas, mist, vapor, or spray. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye or face protection.

### **Environmental Precautions**

Avoid release to the environment. Prevent contamination of ground water.

### Materials and Methods for Containment

#### Small Spills

Use socks/absorbent mini-booms or other inert barrier if necessary to contain small spills.

#### Large Spills

Use large socks/absorbent booms or other inert barrier to form dam/dike in order to contain large spills and prevent further loss.

#### Materials and Methods for Cleanup

## Small Spills

Remove source from area if safe to do so. Use granular sorbent, gel sorbent, vermiculite, cat litter, dirt/earth, pads/rolls, or pillows to absorb spilled material. Remediate affected area as necessary.

## Large Spills

Keep upwind from spill. Remove source from area if safe to do so. Use explosion-proof transfer equipment to recover spilled material. Use granular sorbent, gel sorbent, vermiculite, cat litter, dirt/earth, pads/rolls, or pillows to absorb residual material. Remediate affected area as necessary.

# Section 7 - Handling and Storage

## Precautions for Safe Handling

#### Personal Precautions

Do not handle until all safety precautions have been read and understood. Do not breathe fumes, gas, mist, vapor, or spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye or face protection. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke when using this product.

#### **Environmental Precautions**

Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Special precautions may be necessary for non-conductive containers. Use explosion-proof electrical, ventilation, and lighting equipment. Use only non-sparking tools, such as brass or bronze. Do not pierce or burn, even after use. Avoid release to the environment.

### Conditions and Considerations for Safe Storage

Pressurized container—may burst if heated. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C). Keep out of reach of children. Store locked-up. Store according to NFPA Aerosol Level 2 recommendations.

# Section 8 – Exposure Controls/Personal Protection

| <u>Component</u> | <u>CAS RN</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|------------------|---------------|-----------------|------------------|
| Acetone          | 67-64-1       | 1000 ppm        | 500 ppm          |
| Toluene          | 108-88-3      | 200 ppm         | 20 ppm           |
| 2-Butoxyethanol  | 111-76-2      | 50 ppm          | 20 ppm           |
| Carbon Dioxide   | 124-38-9      | 5000 ppm        | 5000 ppm         |

### **Exposure Controls**

Appropriate Engineering Controls

If practical, use outside with adequate ventilation to minimize exposure.

## PPE Overview

## Hand Protection

Use of chemical-resistant gloves (butyl rubber, EVAL, neoprene, nitrile/Buna-N, PVA, PVC, or Viton) is recommended.

#### Eye Protection

Use of safety glasses with wrap-around lens or goggles is recommended.

#### **Respiratory Protection**

If necessary, use respiratory protection sufficient to reduce exposure to permissible limits.

#### **Additional Protection**

For industrial settings, access to a chemical safety shower with eye wash station is strongly recommended.

# **Section 9 – Physical and Chemical Properties**

Information on Basic Physical and Chemical Properties

Physical State liquid Appearance clear, colorless Odor acetone Odor Threshold 0.5 ppm

pН not relevant **Freezing Point** < -107°F **Boiling Range** 133 - 343°F Flash Point and Method < 20°F by closed-cup tester Explosion Limits in Air 2.1 - 12.7% by volume (composite) **Evaporation Rate** 5.1 (n-Butyl Acetate=1.0) Vapor Pressure, as supplied 80-120 PSI (typical) Vapor Density >1.0 Specific Gravity 0.801 at 68°F <u>Density</u> 6.67 lb/gal at 68°F Water Solubility slightly soluble n-Octanol/Water Partition Coefficient (log Pow) 0.0 (composite) Viscosity 0.4 cSt at 68°F Volatility 100% by weight Auto-ignition temperature 800°F (composite) Other Information

# VOC Content

10% by weight (EPA Method 24)
 10% by weight (consumer products)
 <u>VOC Composite Partial Pressure, PPC</u>
 1.0 mm of Hg at 68°F

# Section 10 - Stability and Reactivity

Chemical Stability under Normal Conditions of Use <u>Chemical Stability</u> Stable under normal conditions of use. <u>Conditions Affording Instability</u>

none known

## Reactivity

not expected

Possibility of Hazardous Reactions none expected

### Conditions to Avoid

Avoid direct sunlight and excessive temperatures. Do not puncture, incinerate, or crush. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. If practical, avoid temperatures exceeding flash point.

### **Incompatible Materials**

strong acids; oxidizers; reducing agents

## Hazardous Decomposition Products

none known

# Section 11 – Toxicological Information

Likely Routes of Exposure ingestion, skin contact, eye contact, inhalation

## Symptoms Related to Physical, Chemical, and Toxicological Characteristics Ingestion Large Quantity gastrointestinal disturbances, including upset stomach, cramping, nausea, vomiting, and diarrhea Small Quantity/Incidental Contact virtually nontoxic after single ingestion of small quantity Skin Contact moderate irritation Eve Contact moderate eye irritation **Inhalation** respiratory tract irritation; headache, lightheadedness; narcotic effects, including dizziness, drowsiness, and loss of coordination Immediate, Delayed, and Chronic Effects SHORT-TERM EXPOSURE Potential Immediate Effects Ingestion drying, burning, or irritation of the mouth and throat, gastrointestinal disturbances, nausea and vomiting Skin Contact drying of the skin Eye Contact temporary corneal damage Inhalation shortness of breath or difficulty breathing, headache, dizziness, nausea and vomiting, drowsiness, fatigue, loss of consciousness, Potential Delayed Effects Ingestion coma, death Skin Contact defatting of the skin, drying and cracking of the skin, aggravation of pre-existing skin conditions Eve Contact temporary corneal damage Inhalation fatique LONG-TERM EXPOSURE Potential Immediate Effects none known Potential Delayed Effects none known Potential Chronic Health Effects Carcinogenicity International Agency for Research on Cancer (IARC) Monographs all components "Group 3 - Not Classifiable as to Human Carcinogenicity" or not listed National Toxicology Program (NTP) Report on Carcinogens not listed Occupational Safety & Health Administration (OSHA) not listed Mutagenicity / Genetic Toxicity not suspected of being a human mutagen / genetic toxicant Teratogenicity not suspected of being a human teratogen **Developmental Effects** possible developmental toxicant (Toluene) **Fertility Effects** not suspected of being a reproductive/fertility toxicant Effects on Lactation

not suspected of affecting lactation

# SPECIFIC TARGET ORGAN TOXICITY (STOT)

# Single Exposure

central nervous system (narcotic effects); respiratory tract (irritation) Repeated Exposure

brain/central nervous system effects

Numerical Measures of Acute Toxicity <u>Oral (Rat)</u> LD<sub>50</sub>: 4300 mg/kg (derived) <u>Dermal (Rabbit)</u> LD<sub>50</sub>: >5000 mg/kg (derived) <u>Inhalation (Rat)</u> LC<sub>50</sub>: 28 mg/L (derived)

Additional Toxicological Information <u>Skin Irritation/Corrosion (Rabbit)</u> skin irritant <u>Serious Eye Damage/Irritation (Rabbit)</u> eye irritant <u>Respiratory Sensitization</u> does not cause respiratory sensitization <u>Skin Sensitization</u> does not cause skin sensitization <u>Aspiration Hazard</u> not an aspiration hazard

# Section 12 - Ecological Information

General Ecological Assessment/Overview

Harmful to aquatic life. Very mobile in soils which may lead to contamination of groundwater.

Aquatic Toxicity Vertebrates (Fish) Acute Toxicity LC<sub>50</sub>: 620 mg/L (derived) **Chronic Toxicity** NOEC: 28 mg/L (derived) Invertebrates (Water Flea) Acute Toxicity LC<sub>50</sub>: 67 mg/L (derived) Chronic Toxicity NOEC: 15 mg/L (derived) Aquatic Plants (Freshwater Algae) Acute Toxicity EC<sub>50</sub>: 39 mg/L (derived) Chronic Toxicity NOEC: 250 mg/L (derived)

Terrestrial Toxicity <u>Invertebrate (Earthworm)</u> LC<sub>50</sub>: 180 mg/L (derived)

Persistence and Degradability <u>Persistence</u> not expected to be persistent

Degradability rapidly degradable

# Bioaccumulative Potential

Bioaccumulation Potential Assessment does not bioaccumulate Bioaccumulation Factor 90 (Toluene)

 Mobility in Soils

 Mobility in Soils Assessment

 very mobile in soils—may contaminate groundwater

 Soil Organic Carbon/Water Partition Coefficient (log Koc)

 1.1 (composite)

### Results of PBT and vPvB Assessment

not a persistent, bioaccumulative, toxic chemical (PBT) not very persistent and very bioaccumulative (vPvB)

## Other Adverse Effects

none known

# Section 13 - Disposal Considerations

## General Assessment/Overview

Dispose of waste in accordance with all applicable regulations. Harmful to aquatic life—do not pour into waterways. Highly flammable liquid and vapor and aggressive solvents, which may dissolve PVC pipes and fittings—do not pour down drain.

## RCRA Hazardous Waste Code(s) (40 CFR 261.20-33)

Based on this material as-supplied, used or unwanted product may be subject to RCRA regulations and classified as F003 – spent non-halogenated solvent mixture containing acetone, methanol, and/or xylene

# Section 14 – Transportation Information

## Transportation by Ground – US Department of Transportation

<u>Shipping Description</u>
 UN1950, Aerosols, 2.1
 <u>Exemption Eligibility</u>
 When shipped by ground, this product may be eligible for a "Limited Quantity" exception per §49 CFR 173.306.

## Transportation by Air - ICAO/IATA

Shipping Description UN1950, Aerosols, 2.1 Exemption Eligibility When shipped by air, this product may be eligible for a "Limited Quantity" exception.

## Transportation by Water - IMO/IMDG

Shipping Description
 UN1950, Aerosols, 2.1
 Exemption Eligibility
 When shipped by water, this product may be eligible for a "Limited Quantity" exception.

# Section 15 – Regulatory Information

Safety, Health, and Environmental Regulations/Legislation

UNITED STATES - SELECT FEDERAL REGULATIONS

Environmental Protection Agency (EPA) Toxic Substances Control Act (TSCA) (15 USC 2601, et seq.) All chemicals known to be present in this product are either listed on the TSCA inventory or are not required to be. SARA Title III (42 USC 9601, et seq.) Section 302 - Extremely Hazardous Substances (40 CFR 355) none Section 304 - Emergency Release Notification (40 CFR 302.4) Acetone, Toluene Section 311/312 – Hazard Categorization (40 CFR 370.40) acute toxicity, chronic toxicity, fire hazard, sudden release of pressure Section 313 – Toxic Chemicals (40 CFR 372.65) Toluene, 2-Butoxyethanol ("certain glycol ethers") Clean Air Act (42 USC 7401, et seq.) Section 112 - Hazardous Air Pollutants Toluene Section 183(e) - Commercial and Consumer Products - VOC Limit and Category (40 CFR 59 subpart C)

75% as "Carburetor and choke cleaner" (complies)

### Occupational Safety & Health Administration (OSHA)

#### Hazard Communication Standard

This safety data sheet (SDS) is provided for compliance with applicable regulations of the Hazard Communication Standard of 2012 (HCS/HAZCOM 2012) found in §29 CFR 1910.1200. Federal law requires persons receiving this document to study it carefully, become aware of the hazards of this product, and notify all employees, visitors, agents, and contractors of the information contained herein.

### Consumer Product Safety Commission

#### Federal Hazardous Substances Act

This product is regulated under the Federal Hazardous Substances Act, is subject to the labeling requirements of 16 CFR 1500, and must include at minimum the following cautionary statements: WARNING: Extremely Flammable. Eye irritant. Contents under pressure. Keep out of the reach of children.

### UNITED STATES – SELECT REGIONAL CONSIDERATIONS

#### Ozone Transport Commission (OTC) - Model Rule VOC Limit and Category

10% as "Carburetor or Fuel-injection Air Intake Cleaner" (complies)

Lake Michigan Air Directors Consortium (LADCO) - Model Rule VOC Limit and Category

45% as "Carburetor or Fuel-injection Air Intake Cleaner" (complies)

## UNITED STATES – SELECT STATE REGULATIONS

### California

### Office of Environmental Health Hazard Assessment (OEHHA)

### Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1986

This product is subject to the labeling requirements of Proposition 65 – Safe Drinking Water and Toxic Enforcement Act of 1986 and must bear the cautionary statement: WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Air Resources Board (ARB/CARB)

### Regulation for Reducing Emissions from Consumer Products - VOC Limit and Category

10% as "Carburetor or Fuel-injection Air Intake Cleaner" (complies)

#### **Massachusetts**

### "Right-to-Know" Legislation – Substance List (105 CMR 670.000)

Acetone, Toluene, 2-Butoxyethanol, Carbon Dioxide

#### New Jersev

### "Right-to-Know" Legislation – Hazardous Substance List (34:5A-1, et seg.)

Acetone, Toluene, 2-Butoxyethanol, Carbon Dioxide

#### Pennsvlvania

### "Right-to-Know" Legislation - Hazardous Substance List (Chapter 323)

2-Propanone, Methylbenzene, 2-Butoxyethanol, Carbon Dioxide

## INTERNATIONAL - SELECT REGULATIONS

### Canada

### Environment Canada - Domestic Substances List (DSL)

All chemicals known to be present in this product are listed on the DSL.

#### China

# Ministry of Environmental Protection – Inventory of Existing Chemical Substances Produced or Imported in China (IECSC)

All chemicals known to be present in this product are listed on the IECSC.

### European Union

## European Chemical Agency - European Inventory of Existing Chemical Substances (EINECS)

All chemicals known to be present in this product are listed on the EINECS.

## Chemical Safety Assessment

has not been conducted on product, as-supplied

# Section 16 – Other Information

Hazardous Materials Information System (HMIS)

| Health               | * 2  | Hazard Index<br>Least - 0 |
|----------------------|------|---------------------------|
| Flammability         | 3    | Slight - 1                |
| Reactivity           | 0    | Moderate - 2              |
| Protective Equipment | nt B | High - 3<br>Extreme - 4   |

## Index of Abbreviations

ACGIH – American Council of Governmental and Industrial Hygienists

CAS RN – Chemical Abstracts Service Registry Number

EC<sub>50</sub> – Median Effective Concentration IATA – International Air Transport Association

ICAO – International Civil Aviation Organization

IMDG – International Maritime Dangerous Goods

IMO – International Maritime Organization

LC<sub>50</sub> – Median Lethal Concentration

LD<sub>50</sub> – Median Lethal Dose

N/A – Not Applicable

NE - Not Established

NOEC – No Observable Exposure Concentration

PEL – Permissible Exposure Limit (as required by OSHA)

TLV - Threshold Limit Value (as recommended by ACGIH)

VOC - Volatile Organic Compound

### **Relevant Dates and Applicability**

Date of Issuance May 28, 2015 Date of Previous Revision not applicable—initial Safety Data Sheet Primary Revision Change(s) not applicable Document Applicability This safety data sheet applies to part numb

This safety data sheet applies to part numbers 0110C, 0113C, 0117C, 0120C, and 0152 manufactured on or after January 1, 2015.

## **Document Author**

Dan Nowlan

### Legal Disclaimer

The information contained in this document is, to the best of Berryman Products, Inc.'s knowledge, complete and accurate but is not warranted. All materials may present unknown hazards and should be used with caution. It is the responsibility of the user to evaluate the information in a prudent manner and to use it in a manner consistent with its intended purpose. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.