HARRIS

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name 1620 Anti-spatter

Version # 01

Issue date 13-February-2014

Revision date Supersedes date -

CAS # Mixture

Product use Protection against weld spatter.

Manufacturer information

Manufacturer/Supplier Harris Products Group

4501 Quality Place Mason, Ohio 45040 US custservmason@jwharris.com

Telephone number 513-754-2000

Emergency Telephone 1-888-60

Numbers

1-888-609-1762 (US, Canada, Mexico only)

Please quote 333988

2. Hazards Identification

Physical state Liquid.

Appearance Clear, colorless liquid.

Emergency overview WARNING

May be harmful if swallowed. May cause central nervous system effects. Causes skin and eye

irritation. Suspect cancer hazard. May cause damage to the liver and kidneys.

OSHA regulatory status

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Eyes Causes eye irritation.
Skin Causes skin irritation.

Inhalation High vapor concentrations are irritating to the eyes, nose, throat, and lungs. Exposure to high

concentrations of vapor or mist may result in CNS effects such as headaches, nausea and

narcosis.

Ingestion May be harmful if swallowed. May cause damage to mucous membranes in nose, throat, lungs

and bronchial system. Breathing product into the lungs during ingestion or vomiting may cause

lung injury and possible death.

Chronic effects Prolonged or repeated exposure may cause liver, kidney, and central nervous system damage.

Signs and symptoms Irritation of eyes and mucous membranes. Skin irritation. Upper respiratory tract irritation.

Headaches, dizziness and nausea.

Potential environmental effects The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

3. Composition / Information on Ingredients

| Components | CAS# | Percent | |
|--------------------|----------|---------|--|
| Methylene chloride | 75-09-2 | 73 - 84 | |
| Carbon dioxide | 124-38-9 | 17 | |

Composition commentsAll concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses

and open eyelids wide apart. Get medical attention if irritation develops or persists.

Skin contact Immediately flush thoroughly with water for at least 15 minutes. Remove contaminated clothing

and shoes. Get medical attention if irritation develops and persists.

Inhalation Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel.

Get medical attention if any discomfort continues.

Ingestion Do not induce vomiting. If vomiting occurs, keep head low so that stomach content does not get

into the lungs. Never give anything by mouth to an unconscious person. Get medical attention.

Notes to physician Treat symptomatically. Symptoms may be delayed.

General advice Show this safety data sheet to the doctor in attendance.

5. Fire Fighting Measures

Flammable properties

Material may burn but not ignite readily.

Extinguishing media

Suitable extinguishing

media

Dry chemical, foam, carbon dioxide.

Unsuitable extinguishing

media

Water or foam (may cause frothing).

Protection of firefighters

Specific hazards arising from the chemical

Heated containers may rupture, explode or be thrown into the air. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

Protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Wear suitable protective equipment.

Fire fighting

equipment/instructions

Hazardous combustion

products

Containers close to fire should be removed or cooled with water.

Product may decompose upon heating to produce phosgene, halogenated compounds, carbon monoxide, and unidentified organic compounds.

6. Accidental Release Measures

Personal precautions Ensure adequate ventilation. Keep unnecessary personnel away. Keep people away from and

upwind of spill/leak. Ventilate closed spaces before entering them. Wear protective clothing as described in Section 8 of this MSDS. Do not touch damaged containers or spilled material unless

wearing appropriate protective clothing.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for cleaning up

Collect for salvage or disposal. Collect any released materials with absorbent, non-combustible material into suitable containers. Clean surface thoroughly to remove residual contamination.

Should not be released into the environment.

7. Handling and Storage

Handling Avoid inhalation of vapors/spray and contact with skin and eyes. When using, do not eat, drink or

smoke. Wear appropriate personal protective equipment (See Section 8). Observe good industrial

hygiene practices.

Storage Keep container tightly closed and in a well-ventilated place. Keep away from incompatible material.

Keep away from food, drink and animal feedingstuffs.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

| Components | Туре | Value | |
|----------------------------------|------|-----------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 30000 ppm | |
| | TWA | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | TWA | 50 ppm | |

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Components | Туре | Value | |
|----------------------------------|-------------------------------|----------|--|
| Methylene chloride (CAS 75-09-2) | STEL | 125 ppm | |
| | TWA | 25 ppm | |
| US. OSHA Table Z-1 Limits for A | Air Contaminants (29 CFR 1910 | 1000) | |
| Components | Туре | Value | |
| Carbon dioxide (CAS | PEL | 5000 ppm | |

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Туре | Value | |
|----------------------------------|------|-------------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 | |
| · | | 30000 ppm | |
| | TWA | 9000 mg/m3 | |
| | | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | TWA | 174 mg/m3 | |
| • | | 50 ppm | |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Туре | Value | |
|----------------------------------|------|-----------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 15000 ppm | |
| | TWA | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | TWA | 25 ppm | |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Туре | Value | |
|-------------------------|------|-----------|--|
| Carbon dioxide (CAS | STEL | 30000 ppm | |
| 124-38-9) | | | |
| | TWA | 5000 ppm | |
| Methylene chloride (CAS | TWA | 50 ppm | |
| 75-09-2) | | | |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Туре | Value | |
|----------------------------------|------|-----------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 30000 ppm | |
| | TWA | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | TWA | 50 ppm | |

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

| Components | Туре | Value | |
|----------------------------------|------|-------------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 | |
| | | 30000 ppm | |
| | TWA | 9000 mg/m3 | |
| | | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | TWA | 174 mg/m3 | |
| , | | 50 ppm | |

Mexico. Occupational Exposure Limit Values

| Components | Туре | Value | |
|----------------------------------|------|-------------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 27000 mg/m3 | |
| | | 15000 ppm | |
| | TWA | 9000 mg/m3 | |
| | | 5000 ppm | |
| Methylene chloride (CAS 75-09-2) | STEL | 1740 mg/m3 | |
| | | 500 ppm | |
| | TWA | 330 mg/m3 | |
| | | 100 ppm | |

Engineering controls

Provide adequate ventilation and minimize the risk of inhalation of vapors and mists. Local exhaust is recommended. Shower, hand and eye washing facilities near the workplace are recommended.

Personal protective equipment

Eye / face protectionWear safety glasses with side shields (or goggles). **Skin protection**Chemical resistant clothing is recommended.

respiratory protection. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA

Standard Z94.4.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance Clear, colorless liquid.

Physical stateLiquid.FormLiquid.ColorColorless.

Odor Characteristic odor.

Odor threshold Not available. pН Not available. Vapor pressure 390 mm Hg Vapor density 1.9 (Air = 1)104 °F (40 °C) **Boiling point** Melting point/Freezing point Not applicable. Solubility (water) Soluble in water. Specific gravity 1.32 (H2O=1) Not available. Flash point

Flammability limits in air, upper, % by volume

Not available.

Flammability limits in air,

lower, % by volume

Not available.

Auto-ignition temperature

Not available.

Evaporation rate 14.5 (Butyl acetate = 1)

10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal temperatures and pressures.

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight.

Incompatible materials Acids, alkalis, oxidizing agents, reactive halogens, or reactive metals.

Hazardous decomposition

products

None under normal temperatures and pressures. In the event of fire: See Section 5.

Possibility of hazardous

reactions

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

11. Toxicological Information

Toxicological data

Components Species Test Results

Methylene chloride (CAS 75-09-2)

Acute

Oral

LD50 Rat 1600 mg/kg

Sensitization Not a skin sensitizer.

Acute effects May be harmful if swallowed. Exposure to high concentrations of vapor or mist may result in CNS

effects such as headaches, nausea and narcosis.

Local effects Components of the product may be absorbed into the body through the skin. Causes skin and eye

irritation.

Chronic effects Prolonged or repeated exposure may cause toxic effects to the central nervous system. Repeated

or prolonged exposure to high concentrations may cause kidney and liver damage.

Carcinogenicity Suspect cancer hazard - may cause cancer.

ACGIH Carcinogens

Methylene chloride (CAS 75-09-2)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methylene chloride (CAS 75-09-2)

2B Possibly carcinogenic to humans.

US NTP Report on Carcinogens: Anticipated carcinogen

Methylene chloride (CAS 75-09-2)

Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene chloride (CAS 75-09-2)

Cancer

Epidemiology No data available. **Mutagenicity** No data available.

Reproductive effects May adversely affect the developing fetus based on animal data.

Further information Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Components Species Test Results

Methylene chloride (CAS 75-09-2)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1250 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 140.8 - 277.8 mg/l, 96 hours

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Environmental effectsAn environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and degradability Not available.

Bioaccumulation / Accumulation

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Methylene chloride (CAS 75-09-2) 1.25

Mobility in environmental

The product is soluble in water.

media

13. Disposal Considerations

Waste codes

US RCRA Hazardous Waste U List: Reference

Methylene chloride (CAS 75-09-2) U080

Disposal instructions Dispose of contents/container in accordance with all local, State and Federal regulations.

Waste from residues / unused

Dispose in accordance with all local, state and federal regulations.

products

14. Transport Information

Basic shipping requirements:

UN number UN1950 Proper shipping name **AEROSOLS**

Hazard class 2.2 Subsidiary hazard class 6.1

Additional information:

306 Packaging exceptions None Packaging non bulk Packaging bulk None

2.2, 6.1

IATA

UN1950 **UN number UN proper shipping name AEROSOLS**

Transport hazard class(es) 2.2 Subsidiary class(es) 6.1

IMDG

UN number UN1950 **UN proper shipping name AEROSOLS**

Transport hazard class(es) 2.2 Subsidiary class(es) 6.1

TDG

UN1950 **UN** number Proper shipping name **AEROSOLS**

Hazard class Subsidiary hazard class 6.1 Marine pollutant No

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methylene chloride (CAS 75-09-2)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Methylene chloride (CAS 75-09-2)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methylene chloride (CAS 75-09-2) Listed.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Methylene chloride: 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Not controlled **Drug Enforcement**

Administration (DEA) (21 CFR

1308.11-15)

1620 Anti-spatter 6/7

916281 Version #: 01 Revision date: -Issue date: 13-February-2014 Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the MSDS

contains all the information required by the CPR.

WHMIS status Controlled

WHMIS classification D2A - Other Toxic Effects-VERY TOXIC

D2B - Other Toxic Effects-TOXIC

WHMIS labeling



Inventory status

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Hazardous Substances (Director's): Listed substance

Carbon dioxide (CAS 124-38-9)

Methylene chloride (CAS 75-09-2)

Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Methylene chloride (CAS 75-09-2) Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylene chloride (CAS 75-09-2) Listed: April 1, 1988 Carcinogenic.

US. Massachusetts RTK - Substance List

Carbon dioxide (CAS 124-38-9)

Methylene chloride (CAS 75-09-2)

Listed.

US. New Jersey Worker and Community Right-to-Know Act

Carbon dioxide (CAS 124-38-9) Methylene chloride (CAS 75-09-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon dioxide (CAS 124-38-9) Methylene chloride (CAS 75-09-2)

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

A HMIS® Health rating including an * indicates a chronic hazard.

HMIS® ratings Health: 2*

Flammability: 1 Physical hazard: 0

NFPA Ratings



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.

1620 Anti-spatter CPH MSDS NA

916281 Version #: 01 Revision date: - Issue date: 13-February-2014

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).