LOCTITE CORPORATION 09/11/96 ROCKY HILL, CONNECTICUT 06067 EMERGENCY PHONE: (860) 571-5100 MATERIAL SAFETY DATA SHEET Page 01 of 05 Ultra Blue(R) Sensor-Safe RTV Silicone Gasket 81724 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION Ultra Blue(R) Sensor-Safe RTV Silicone Gasket Product Name: Maker Item No.: 81724 Part No.: 77BR Product Type: RTV Silicone COMPOSITION, INFORMATION ON INGREDIENTS 2. Ingredients CAS No. % Poly(dimethylsiloxane), hydroxy terminated 70131-67-8 35-40 Calcium carbonate 471-34-1 30-35 Poly(dimethylsiloxane), dimethyl 63148-62-9 15-20 Modified silicon dioxide 5-10 68611-44-9 Vinyl oximinosilane 2224-33-1 3-5 Substituted silane Proprietary 0.1-1 * * * Methyl ethyl ketoxime Proprietary ***When this product is exposed to moisture, 5-10% methyl ethyl ketoxime may be formed. Ingredients which have exposure limits Exposure Limits (TWA) ACGIH OSHA OTHER Ingredients (TLV) (PEL) Calcium carbonate 10 mg/m3 dust 15 mg/m3 dust None 5 mg/m3 respir. 10 mg/m3 6 mg/m3 Modified silicon dioxide 6 mg/m3 Methyl ethyl ketoxime None None 3 ppm TWA 10 ppm STEL ACGIH OSHA Exposure Limits (STEL) Ingredients (TLV) (PEL)

3. HAZARDS IDENTIFICATION

Toxicity: Eye and skin irritant. Moderately toxic by ingestion. When heated to temperatures above 300°F (150°F) in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin

LOCTITE CORPORATION 09/11/96 ROCKY HILL, CONNECTICUT 06067 EMERGENCY PHONE: (860) 571-5100 MATERIAL SAFETY DATA SHEET Page 02 of 05 Product Name: Ultra Blue(R) Sensor-Safe RTV Silicone Gasket Maker Item No.: 81724 3. HAZARDS IDENTIFICATION (continued) and respiratory sensitizer. Vapors irritate eyes, nose and throat. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. Primary Routes of Entry: Skin absorbtion, ingestion, inhalation. Signs and symptoms of Exposure: Methyl ethyl ketoxime produced during cure is toxic and irritates eyes, nose and throat. Existing Conditions Aggravated by Exposure: Dermatitis Literature Referenced Carcinogen Target Organ and Other Health Effects NTP IARC OSHA Ingredients Poly(dimethylsiloxane), hydroxy terminated No Data NO NO NO NUI Calcium carbonate NO NO NO Poly(dimethylsiloxane), dimethyl_____Modified silicon dioxideNo DataWinnel oviminosilaneNo Data dimethyl IRR NO NO NO NO NO NO NO NO NO Substituted silaneNo DataMethyl ethyl ketoximeALG BLO CNS IRR Substituted silane NO NO NO NO NO NO Abbreviations BLO Blood ALG Allergen CNS Central nervous system IRR Irritant NUI Nuisance dust 4. FIRST AID MEASURES Do not induce vomiting. Keep individual calm. Ingestion: Obtain medical attention Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention. Wipe off paste with paper towel or cloth. Skin Contact: Wash thoroughly with soap and water Flush at least 15 minutes with water. Obtain Eye Contact: medical attention.

LOCTITE CORPORATION 09/11/96 ROCKY HILL, CONNECTICUT 06067 EMERGENCY PHONE: (860) 571-5100 MATERIAL SAFETY DATA SHEET Page 03 of 05 Product Name: Ultra Blue(R) Sensor-Safe RTV Silicone Gasket Maker Item No.: 81724 5. FIRE FIGHTING MEASURES Flash Point: More than 200°F Method: Tag Closed Cup Recommended Carbon dioxide, foam, dry chemical Extinguishing Agents: Hazardous Products formed by Fire or Thermal Decomp Formaldehyde, silica fume Unusual Fire or Explosion Hazards: None Explosive Limits: (% by volume in air)Lower Not available (% by volume in air)Upper Not available 6. ACCIDENTAL RELEASE MEASURES Steps to be taken in case of spill or leak: Wipe or scrape up spilled material. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber. 7. HANDLING AND STORAGE Store in a dry area below 90°F. Keep Safe Storage: containers closed when not in use. (Contact Loctite Customer Service 1-800-243-4874 for shelf Life information) Avoid skin and eye contact. Avoid breathing vapor Handling: Do not wear contact lenses while applying material Vapor may be trapped under lens. EXPOSURE CONTROLS, PERSONAL PROTECTION 8. Eyes: Safety glasses or goggles. Skin: Rubber or plastic gloves. Ventilation: Provide local ventilation for prolonged use in a confined area. See Section 2 for Exposure Limits. 9. PHYSICAL AND CHEMICAL PROPERTIES Appearance: Blue paste Mild Odor: Boiling Point: Not Applicable, Polymeric рH: 7-8 Solubility in Water: Polymerized Specific Gravity 1.3

LOCTITE CORPORATION 09/11/96 ROCKY HILL, CONNECTICUT 06067 EMERGENCY PHONE: (860) 571-5100 MATERIAL SAFETY DATA SHEET Page 04 of 05 Product Name: Ultra Blue(R) Sensor-Safe RTV Silicone Gasket Maker Item No.: 81724 9. PHYSICAL AND CHEMICAL PROPERTIES (continued) Volatile Organic Compound (EPA Method 24) 3.9%; 50.7 grams per liter Vapor Pressure: Less than 5mm at 70°F Vapor Density: 3.0 Evaporation Rate Not available (Ether = 1)10. STABILITY AND REACTIVITY Stability: Stable Hazardous Polymerization: Will not occur Incompatibility: Strong oxidizers. Polymerized by contact with moisture. Hazardous Decomposition Products (non-thermal): Methyl ethyl ketoxime 11. TOXICOLOGICAL INFORMATION See Section 3. 12. ECOLOGICAL INFORMATION No data available 13. DISPOSAL CONSIDERATIONS Recommended methods of disposal: Cured rubber can be incinerated following EPA and local regulations EPA Hazardous Waste Number NH - Not a RCRA Hazardous Waste Material 14. TRANSPORT INFORMATION DOT (49 CFR 172) Domestic Ground Transport Proper Shipping Name: Unrestricted Hazard Class or Division: Unrestricted Identification Number: None Marine Pollutant: None ΤΔͲΔ Proper Shipping Name: Unrestricted Class or Division: Unrestricted UN or UD Number: None UN or ID Number: None

LOCTITE CORPORATION		09/11/96
	ROCKY HILL, CONNECTICUT 06067	
	EMERGENCY PHONE: (860) 571-5100	
	MATERIAL SAFETY DATA SHEET	Page 05 of 05
Product Name:	Ultra Blue(R) Sensor-Safe RTV Maker	Silicone Gasket
Item No.:	81724	
15. REGULATORY INFORMATION		
CA Proposition 65:	No Prop65 chemicals are known	to be present.
16. OTHER INFORMATION		
Estimated NFPA(R) Code: Health Hazard: Fire Hazard: Reactivity Hazard: Specific Hazard:	1 1 O No water.	
	1 1 0 See Section 8. trademark of the National Fire	
HMIS is a registered Prepared By: Title: Company: (24hr.) Phone: Revision Date:	trademark of the National Paint and Coatings Assn. Stephen Repetto Research Chemist, Environmental Health & Safety Loctite Corp., 1001 Tr Br Cr, Rocky Hill CT 06067 (860) 571-5100 January 22, 1996 Revision: 0031	