

1696 West Grand Avenue, Oakland, CA 94607-1607 Tel (510) 839-1000 - Fax (510) 839-1090

Commercial and Industrial Water Treatment Programs Since 1927

Product Information:

| Trade Name (as labeled): | SKASOL CCC-7 | |
|---------------------------------------|--------------------------------|--|
| Manufacturer's Name: | Skasol Incorporated | |
| Address (complete mailing address): | 1696 West Grand Avenue | |
| | Oakland, California 94607-1607 | |
| 24 Hour Emergency Telephone: | (800) 424-9300 | |
| Information Telephone: (510) 839-1000 | | |
| Date prepared or revised: | July 10, 2006 | |
| Name of preparer: Michelle Navasca | | |

Hazardous Ingredients:

| Chemical Name | CAS Number | Percent | Limits in Air | (give units) | |
|---------------------------|------------|---------|---------------|--------------|-----------------|
| | | | ACGIH TLV | OSHA PEL | Other (specify) |
| 2- (Diethylamino) Ethanol | 100-37-8 | < 30% | 10ppm | | |

Physical Properties:

| yo.ou oportio | • | | |
|-------------------------------|---------------|---------------------------------------|----------------|
| Vapor Density: | Not available | Melting Point or Range: | Not applicable |
| Specific Gravity: | 0.98 | Boiling Point or Range, °F: | 218 |
| Solubility in Water: | Complete | Evaporation Rate: | Not available |
| Vapor pressure: | Not available | | |
| Appearance and Odor: | | Clear red liquid, ammoniacal odor. | |
| How to detect this substance: | | High pH will cause irritation with an | y contact. |

Fire and Explosion:

| Flash point, °F (give method): | None |
|--------------------------------|------|
| Auto ignition temperature, °F: | None |

| Flammable limits in air, volume %: | None Lower (L | EL) Upper (UEL) | |
|------------------------------------|---------------|-----------------|--|

Fire extinguishing materials:

| I II O OALIIIŞ | gaioning ma | toriaio. | | | | | | | |
|----------------|--------------|--------------|-----------|-----------------|---------------|----------------------|---|-------|--|
| Water | Х | Foam | Х | CO ₂ | Х | Dry Chemical | Х | Other | |
| Special fire | fighting pro | cedures: | Wear full | protective clot | hing and resp | piratory protection. | | | |
| Unusual fir | e and explos | ion hazards: | None. | | | | | | |

Health Hazard Information:

| Symptoms of overexposure for each potential route of exposure. | | | | |
|--|--|--|--|--|
| Inhaled: | Mist or liquid will cause some minor irritation of the respiratory tract. Large amount will cause burning. | | | |
| Contact with skin or eyes: | Causes severe burning to eyes. Skin is more resistant, but prolonged exposure can cause irritation. | | | |
| Absorbed through skin: | Not absorbed. | | | |
| Swallowed: | Will cause burning damage to mouth, esophagus, stomach, etc. May cause nausea. | | | |

| HEALTH HAZA | ARD |
|------------------------------|-------------------|
| Deadly | \ / \ / |
| 3. Extreme Ha | zard |
| 2. Hazardous | |
| 1. Slightly Haz | ardous red |
| 0. Normal Mate | erial blue vellow |
| SPECIFIC HAZ | ZARD V |
| Oxidizer | while |
| 3. Acid | \ \ \ |
| 2. Alkali | |
| 1. Corrosive | ~ |
| 0. Use no wate | r |

- FIRE HAZARD

 4. Below 73 degree F (Boiling pt. below 100 degree F)

 3. Below 73 degree F (Boiling pt. at/above 100 degree F and/or at/above 73 degree F not exceeding 100 degree F)

 2. Above 100 degree F not exceeding 200 degree F
- Above 100 degree F
 Will not burn
- REACTIVITY

- 4. May detonate
 3. Shock and heat may detonate
 2. Violent chemical change
 1. Unstable if heated
 0. Stable

| Health Hazard | 2 |
|-------------------|---|
| Fire Hazard | 1 |
| Reactivity Hazard | 2 |
| Specific Hazard | 2 |



1696 West Grand Avenue, Oakland, CA 94607-1607 Tel (510) 839-1000 - Fax (510) 839-1090

Commercial and Industrial Water Treatment Programs Since 1927

Health Hazard Information (continued):

Heath effects or risks from exposure:

| Acute: | /ill cause burns with acute exposure. | |
|----------|--|--|
| Chronic: | ame as acute, but with milder symptoms | |

First Aid Emergency Procedures:

| I II St Ala Elli | signify i roccures. |
|------------------|---|
| Eye Contact: | Immediately flush with plenty of water, raising eyelids often to help irrigation and continue for at least 15 minutes. Get medical assistance. |
| Skin Contact: | Flush with plenty of water. Remove contaminated clothing. If skin is slippery alkalinity is still present. Continue rinsing until slipperiness is gone. |
| Inhaled: | Remove to fresh air. If not breathing give artificial respiration (preferably mouth to mouth). Call a physician or poison control center. |
| Swallowed: | If conscious drink large quantities of water or milk. Do not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person. |

Suspected cancer agent?

| Х | No: This product's ingredients are not found in the lists below. |
|---|--|
| | |

| Federal OSHA | National Toxicology Program | International Assoc. For Research On Cancer |
|--------------|-----------------------------|---|
| | | |

Medical Conditions Aggravated By Exposure Not Known

Reactivity Data:

Stability:

| Х | Stable | Unstable | | |
|--|-----------|-----------------------------|------|--|
| Conditions | to avoid: | Do not mix with strong acid | le . | |
| Conditions to avoid: Incompatibility (materials to avoid): | | Strong acids. | 15. | |
| Hazardous decomposition products: | | Heat | Heat | |

| Hazardous polymerization: | May occur | Х | will not occur |
|---------------------------|--|---|----------------|
| | | | |
| Conditions to avoid: | to avoid: Do not store near excessive heat sources | | |

Spill, Leak and Disposal Procedures:

| Spill response procedures: | Dike area to contain the spill. Small spills may be flushed and diluted with lots of water and washed to | |
|--------------------------------|--|--|
| | a sewer connected to a waste treatment plant. | |
| Preparing wastes for disposal: | Larger spills should be contained and neutralized with dilute acid to a neutral pH (6.0-9.0) before washing with plenty of water to a sewer connected to a waste treatment plant. Any DOT container is suitable for temporarily holding neutralized waste. | |

Special Handling Information:

| Ventilation and Engineering Controls: | Local exhaust ventilation should be sufficient to minimize employee exposure excessive dust. |
|---------------------------------------|---|
| Respiratory Protection: | When conditions require it, use a respirator approved by NIOSH/MSHA with a dust/mist filter. Respiratory protection programs must meet or exceed the requirements of Title 29 CFR 1910.134 |
| Eye Protection: | Close fitting chemical safety goggles with a face shield if needed. |
| Gloves: | Nitrile, neoprene or natural rubber. |
| Other Clothing and equipment | Rubber boots with safety toes, rubber aprons, plastic hard hats should be used when necessary to prevent skin contact. |
| Work practices, hygienic practices: | Protective clothing and use of equipment must be in accordance with Title 29 CFR Sections 1910.132 and 1910.133 |
| Other Handling and Storage Needs: | Provide emergency eye wash stations and emergency shower facilities near use and handling areas. |
| Measures during Maintenance: | Chemical feed pumps should be routinely washed out with water. Plastic tubing and fittings should be frequently inspected for leaks and clogs. As with all automatic equipment, be certain that the power is disconnected before performing any adjustments or repairs. Use all above precautions. |
| Disclaimer: | All information, recommendations and suggestions appearing in this MSDS concerning the use of our products are based upon tests and data believed to be reliable. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals reading this information must exercise their independent judgment when determining its appropriateness for a particular purpose. |