Date:5/1/99

MATERIAL SAFET 3-6570 BRILLIANT SI		_	OI	BSOLETE	:	Revision	Da	
Section I - Produc								
			CHEMTR	Emergency Phone Number (24 CHEMTREC @ (800)424-9300 - MSDS Request Phone Number:				
			1-800-	1-800-752-5139, Ext. 2745				
			i					
				Date Prepared: February 8, 1995 -				
Product Use: OFFSET PRINTING								
Chemical Name, Trad	ie Name,	Synonyms:	SHEET FED	OFFSET I	NK.			
HMIS RATING 1 - Health 1 -		oility 0	- Reactiv	ity A -	- Personal P	rotection		
Section II - Hazar								
Hazardous Components		_		OSHA PE	kposure Limi EL ACGIH TL	V OTHER		
CONTAINS NO KNOWN HAZARDOUS MATERIALS	S	N.A.	 N.A.	 N.A.	N.A			
	į		İ	i i				
			1	I				
			İ	I				
Section III - Physi	 ical Data 527-590	a	 Hq: N.	 				
Boiling POINT(F):	527 - 590		 pH: N. Freezing	A. Point(F)): N.A.			
Boiling POINT(F): Vapor Pressure(mm H	527-590 Ig): UNKN	OWN	Freezing	Point(F)): N.A.		 	
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR	527-590 Hg): UNKN	OWN	Freezing % Volati	Point(F)	N.A. lume: 20			
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H	527-590 Ig): UNKN = 1): > 120=1): >	10WN 1	Freezing % Volati Color An	Point(F) le By Vol d Odor: S	N.A. lume: 20 SILVER / OIL	 Y 		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR	527-590 Hg): UNKN = 1): > H2O=1): >	OWN 1 1 1	Freezing % Volati Color An Physical	Point(F) le By Vol d Odor: S	N.A. lume: 20 SILVER / OIL	 Y 		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D	527-590 ag): UNKN = 1): > 120=1): > 3utyl Ace	OWN 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Freezing % Volati Color An Physical	Point(F) le By Vol d Odor: S	N.A. lume: 20 SILVER / OIL	 Y 		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a	527-590 ag): UNKN = 1): > 120=1): > Butyl Ace :: INSOUL	OWN 1 tate = 1): BLE.	Freezing % Volati Color An Physical N.A.	Point(F)	N.A. lume: 20 SILVER / OIL	 Y 		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water	527-590 ag): UNKN = 1): > 120=1): > 3utyl Ace :: INSOUL and Exp	own tate = 1): BLE. losion Ha	Freezing % Volati Color An Physical N.A.	Point(F)	lume: 20 SILVER / OIL PASTER Limits:	Y		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a FLASH POINT (METHOD	527-590 Hg): UNKN = 1): > 120=1): > Butyl Ace :: INSOUL :: INSOUL :: USED): 265).	tate = 1):	Freezing	Point(F)	lume: 20 SILVER / OIL PASTER Limits: UEL:	Y		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a FLASH POINT (METHOD 270 (F) (JIS-K22	527-590 ag): UNKN = 1): > 120=1): > 3utyl Ace :: INSOUL and Exp 0 USED): 265). erature:	tate = 1): BLE. N.D.	Freezing % Volati Color An Physical N.A.	Point(F)	lume: 20 SILVER / OIL PASTER Limits: UEL:	Y		
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a FLASH POINT (METHOD 270 (F) (JIS-K22 Auto-ignition Tempe	527-590 Hg): UNKN = 1): > 120=1): > Butyl Ace :: INSOUL and Exp USED): 265). Prature:	OWN 1 tate = 1): BLE. Ilosion Ha	Freezing % Volati Color An Physical N.A.	Point(F)	Limits:	Y	 	
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a FLASH POINT (METHOD 270 (F) (JIS-K22 Auto-ignition Tempe	527-590 ag): UNKN = 1): > 120=1): > 3utyl Ace :: INSOUL and Exp USED): 1:65). ar: FOAM / ang Proce	own 1 tate = 1): BLE. losion Ha N.D. CO2 / DRY dures: CO0 Hazards: D	Freezing % Volati Color An Physical N.A. Image: An an an an an an an an an an an an an an	Point(F) le By Vol d Odor: S State: I lammable EL: 1.1 RS EXPOSE	Limits: UEL: Description:	Y	ER	
Boiling POINT(F): Vapor Pressure(mm H Vapor Density (AIR Specific Gravity (H Odor Threshold: N.D Evaporation Rate (B Solubility in Water Section IV - Fire a FLASH POINT (METHOD 270 (F) (JIS-K22 Auto-ignition Tempe Extinguishing Media Special Fire Fighti Unusual Fire And Ex CLOSED CONTAINERS M	527-590 lig): UNKN = 1): > 20=1): > 20=1): > Livity Ace Serature: Arrang Proce Sivity Da	OWN 1 tate = 1): BLE. Ilosion Ha N.D. CO2 / DRY dures: CO0 Hazards: D DDE WHEN EX	Freezing % Volati Color An Physical N.A. Image: All Color An	Point(F) le By Vol do Odor: S State: I lammable EL: 1.1 RS EXPOSE MAY BE (XTREME HE	Limits: UEL: Description:	UNKNOWN WITH WAT	ER	

MATERIAL SAFETY DATA SHEET OBSOLETE 3-6570 BRILLIANT SILVER OFFSET INK Revision Date:5/1/99 Incompatibility (Materials to Avoid): NONE. Hazardous Decomposition Products: DENSE SMOKE WHEN BURNING. |Conditions to Avoid: NONE. Hazardous | May Occur: Polymerization | Will Not Occur: X Section VI - Health Hazard Data (Acute and Chronic) Primary Route(s) of Entry: DERMAL. Oral Ingestion: NOT KNOWN. Eve Contact: MAY CAUSE IRRITATION. Skin Contact: MAY CAUSE IRRITATION WITH PROLONED OR REPEATED CONTACT. Inhalation: NOT KNOWN TO BE A PROBLEM. Effects of Overexposure: PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN TRRTTATTON. Medical Conditions Generally| NONE KNOWN. Aggravated by Exposure Carcinogenicity: NOT KNOWN TO BE CARCINOGENIC. Mutagenicity: NOT KNOWN TO BE MUTAGENIC. Teratogenicity: NOT KNOWN TO BE TERATOGENIC. Reproductive Toxicity: NOT KNOWN TO HAVE REPRODUCTIVE TOXICITY. FIRST AID PROCEDURES Ingestion: DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN FOR MEDICAL ADVISE. Eye: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISITS CALL A PHYSICIAN Skin: REMOVE IMMEDIATELY AND WASH WITH SOAP AND WATER. Inhalation: REMOVE FROM EXPOSURE. Section VII - Toxicology Information Inhalation Oral DCIMET Inc50 LD50 (RATS) LD50 (RABBITS) Ingredient N.A. N.A. N.A. N.A.

Section VIII - Spill or Leak Procedure

Steps to be taken in case material is released or spilled: WIPE UP AND DISPOSE OF WITH SOLID WASTE. IF SOLVENT WETTED WIPES WERE USED DISPOSE OF IN APPROVED CONTAINERS.

MATERIAL SAFETY DATA SHEET

OBSOLETE

3-6570 BRILLIANT SILVER OFFSET INK Revision Date:5/1/99 Disposal Method: IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS FOR NON-FLAMMABLE OILY WASTE.

Section IX - Special Protection Information

Ventilation Local Exhaust: N.A. Special: N.A. Mechanical(General): ACCEPTABLE. Other: N.A.

Respiratory Protection: NOT NORMALLY REQUIRED.

Protective Clothing: GLOVES WHERE PROLONGED CONTACT IS POSSIBLE.

Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment: NONE.

Section X - Special Precautions

Precautions to be taken in Handling and Storing: KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT SOURCES AND FLAME.

Other Precautions: DO NOT TRANSFER TO UNMARKED CONTAINERS.

Section XI - Transportation Information

Hazard Class: N.A.

DOT Proper Shipping Name: NOT REGULATED.

Section XII - Regulatory Information

CERCLA/SUPERFUND, 40 CFR 117,302: THIS PRODUCT DOES NOT CONTAIN ANY REPORTABLE QUANTITY (RQ) SUBSTANCE.

SARA(TITLE III) - Sections 302, 311, 312, and 313:

Section 302 Extremely Hazardous Substances (40 CFR 355): THIS PRODUCT DOES NOT CONTAIN ANY INGREDIENTS LISTED AS AN EXTREMELY HAZARDOUS SUBSTANCE.

Section 311 and 312 MSDS Submission and Inventory Reporting (40 CFR 370): THIS PRODUCT MAY REQUIRE REPORTING UNDER 311 AND 312.

Section 313 Toxic Chemical Release Reporting (40 CFR 372): THIS PRODUCT DOES NOT CONTAIN ANY INGREDIENTS ON THE LIST OF TOXIC CHEMICALS.

TOXIC SUBSTANCES CONTROL ACT (TSCA):

This product complies with rules and regulations of TSCA.

California Proposition 65: THIS PRODUCT DOES NOT CONTAIN ANT MATERIAL, THAT ARE CURRENTLY LISTED BY THE STATE OF CALIFORNIA UNDER PROPOSITION 65.

Section XIII - Addition Information

NONE

 ${\tt N.D.}={\tt No}$ Data ${\tt N.A.}={\tt Not}$ Applicable The information herein given in good faith but no warranty, express or implied, is made.