

## CUSTOM BUILDING PRODUCTS INC -- INTERIOR SPACKLING PASTE -- 8010-00N079258

## ===== Product Identification =====

Product ID:INTERIOR SPACKLING PASTE  
MSDS Date:05/02/1995  
FSC:8010  
NIIN:00N079258  
MSDS Number: CGGYH  
=== Responsible Party ===  
Company Name:CUSTOM BUILDING PRODUCTS INC  
Address:6511 SALT LAKE AVE  
City:BELL  
State:CA  
ZIP:90201  
Country:US  
Info Phone Num:213-582-0846  
Emergency Phone Num:213-582-0846  
Preparer's Name:STEVE TAYLOR  
CAGE:CUSTO

=== Contractor Identification ===  
Company Name:CUSTOM BUILDING PRODUCTS  
Address:6511 SALT LAKE AVE.  
City:BELL  
State:CA  
ZIP:90201  
Country:US  
Phone:213-582-0846  
CAGE:CUSTO

## ===== Composition/Information on Ingredients =====

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA). VP:0.1 @ 68F.  
LD50: (ORAL,RAT) 6,000-13,000 MG/KG.  
CAS:107-21-1  
RTECS #:KW2975000  
OSHA PEL:N/K  
ACGIH TLV:50 PPM, VAPOR, C  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM CARBONATE  
CAS:1317-65-3  
RTECS #:EV9580000  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:VM & P NAPHTHA; (ALIPHATIC HYDROCARBONS). VP:15 @ 68F.  
CAS:64742-89-8  
OSHA PEL:500 PPM (MFR)  
ACGIH TLV:N/K

Ingred Name:ACRYLIC COPOLYMERS  
OSHA PEL:N/K  
ACGIH TLV:N/K

## ===== Hazards Identification =====

LD50 LC50 Mixture:SEE INGREDIENT 1.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INHALATION:VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS. SKIN CONTACT:IRRITATING UPON REPEATED OR PROLONGED CONTACT. EYE CONTACT:SLIGHT (TEMPORARY) IRRITATION. CORNEAL INJURY IS UNLIKELY. SKIN ABSORPTION:REPEATED EXPOSURE TO LARGE QUANTITIES MAY RESULT IN (EFFECTS OF OVEREXPOSURE)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HEALTH HAZARD:ABSORPTION OF HARMFUL AMOUNTS.

INGESTION:AMOUNTS INGESTED INCIDENTAL TO INDUSTRIAL HANDLING NOT LIKELY TO CAUSE INJURY; HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY, EVEN DEATH. CHRONIC:EXCESSIVE EXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM, KIDNEY, BLOOD & POSSIBLE LIVER EFFECTS.

Medical Conditions Aggravated by Exposure:PRE-EXISTING SKIN, EYE & RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO ETHYLENE GLYCOL.

===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEE MD IF IRRITATION RESULTS. SKIN:WASH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION RESULTS. INHALATION:REMOVE TO FRESH AIR. INGESTION:IMMEDIATELY INDUCE VOMITING BY GIVING TWO GLASSES OF WATER & STICKING FINGER DOWN THROAT. CALL MD.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:FOAM, CO<sub>2</sub>, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. CLOSED CONTAINERS MAY RUPTURE IF EXPOSED TO EXTREME TEMPERATURES.

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOVE 100C/212F. ACRYLIC POLYMER FILM CAN BURN & CONTAINERS MAY RUPTURE IF EXPOSED TO EXTREME TEMPERATURES.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID ENTRY INTO SEWERS OR NATURAL WATERWAYS. SMALL SPILLS:SOAK UP WITH ABSORBENT MATERIAL. LARGE SPILLS:DIKE & PUMP INTO SUITABLE CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA OUT OF SUNLIGHT. STORE AWAY FROM HEAT OR ANY HEAT SOURCES. PROTECT FROM FREEZING.

Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE MAY EXCEED TLV VALUE, USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation:GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP VAPOR CONCENTRATIONS WITHIN SPECIFIED TLV RANGES.

Protective Gloves:PLASTIC OR RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES.

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . ADEQ CLTHG SHOULD BE WORN TO PVNT SKIN CONT.  
Work Hygienic Practices:HYGIENE & GOOD HOUSEKEEPING PRACTICES SHOULD BE OBSERVED.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C  
Vapor Pres:SEE INGS  
Vapor Density:HVR/AIR  
Spec Gravity:1.6 (H\*20=1)  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SOLUBLE UNTIL DRIED  
Appearance and Odor:WHITE, CREAMY PASTE; MILD ACRYLIC ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT W/STRONG OXIDIZING MATERIALS. ETHYLENE GLYCOL WILL REACT VIOLENTLY W/CHLOROSULFONIC ACID, OLEUM, H2SO4.  
Stability Condition to Avoid:NONE KNOWN.  
Hazardous Decomposition Products:THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE &/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PRODUCT I/A/W APPLICABLE LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.